



MLFB-Ordering data: 1LE1002-0DB22-2AA4

Motor type: 1AV1082B

Client order no.:

Item no.:

Order no.:

Consignment no.:

Offer no.:

Project:

Remarks:

U [V]	Δ/Y	f [Hz]	P		I [A]	n [1/min]	M [Nm]	NOM. EFF at ... load [%]			Power factor at ... load			I _A /I _N I _f /I _N	M _k /M _N T _f /T _N	M _v /M _N T _v /T _N	IE-CL
			[kW]	[hp]				4/4	3/4	2/4	4/4	3/4	2/4				
230	Δ	50	0.55	- / -	2.50	1385	3.8	70.0	70.7	67.7	0.79	0.69	0.55	3.7	2.1	2.2	IE1
400	Y	50	0.55	- / -	1.44	1385	3.8	70.0	70.7	67.7	0.79	0.69	0.55	3.7	2.1	2.2	IE1
460	Y	60	0.63	- / -	1.37	1685	3.6	74.0	74.2	71.4	0.78	0.69	0.56	4.3	2.3	2.5	IE1
IM B3 / IM 1001		FS 80 M		IP55		CC032A		IEC/EN 60034		IEC, DIN, ISO, VDE, EN							

Mechanical data		Terminal box	
Sound pressure level 50Hz/60Hz (load)	53 dB(A) 55 dB(A)	Terminal box position	top
Moment of inertia	0.00284 kg m ²	Material of terminal box	Aluminium
Bearing DE NDE	6004 2Z C3 6004 2Z C3	Type of terminal box	TB1 E00
Bearing lifetime	40000 h	Contact screw thread	M4
Lubricants	Esso Unirex N3	Max. cross-sectional area	1.5 mm ²
Regreasing device	No	Cable diameter from ... to ...	9.0 mm - 17.0 mm
Grease nipple	- / -	Cable entry	1xM25x1,5
Type of bearing	Preloaded bearing DE	Cable gland	1 plug
Condensate drainage holes	No	Special design (0)	
External earthing terminal	No		
Vibration class	A		
Insulation	155(F) to 130(B)		
Duty type	S1		
Direction of rotation	bidirectional		
Frame material	aluminum		
Data of anti condensation heating	- / -		
Coating (paint finish)	Standard paint finish C2		
Color, paint shade	RAL7030		
Motor protection	(A) without (Standard)		
Method of cooling	IC411 - self ventilated, surface cooled		
Environmental conditions			
Ambient temperature	-20 °C - +40 °C		
Altitude above sea level	1000 m		

