

3RW40566BB44
Siemens soft starter

GENERAL SPECIFICATIONS

Specification	Value
product brand name	SIRIUS
product designation	Soft starter

PRODUCT FEATURE

Specification	Value
integrated bypass contact system	Yes
thyristors	Yes
intrinsic device protection	Yes
motor overload protection	Yes
evaluation of thermistor motor protection	No
external reset	Yes
adjustable current limitation	Yes

GENERAL TECHNICAL DATA

Specification	Value
product function inside-delta circuit	No
product component motor brake output	No
insulation voltage rated value	600 V
degree of pollution	3, acc. to IEC 60947-4-2
reference code according to EN 61346-2	Q
reference code according to DIN 40719 extended according to IEC 204-2 according to IEC 750	G

POWER ELECTRONICS

Specification	Value
operational current at 40 °C rated value	162 A
operational current at 50 °C rated value	145 A
operational current at 60 °C rated value	125 A
yielded mechanical performance for 3-phase motors at 230 V at standard circuit at 40 °C rated value	45 kW
yielded mechanical performance for 3-phase motors at 400 V at standard circuit at 40 °C rated value	90 kW
yielded mechanical performance [hp] for 3-phase AC motor at 200/208 V at standard circuit at 50 °C rated value	40 hp
operating frequency rated value	50 ... 60 Hz
relative negative tolerance of the operating frequency	-10 %
relative positive tolerance of the operating frequency	10 %
operating voltage at standard circuit rated value	200 ... 460 V
relative negative tolerance of the operating voltage at standard circuit	-15 %

POWER ELECTRONICS

Specification	Value
relative positive tolerance of the operating voltage at standard circuit	10 %
minimum load [%]	20 %
adjustable motor current for motor overload protection minimum rated value	87 A
continuous operating current [% of Ie] at 40 °C	115 %
power loss [W] at operational current at 40 °C during operation typical	75 W

CONTROL CIRCUIT/ CONTROL

Specification	Value
type of voltage of the control supply voltage	AC
control supply voltage frequency 1 rated value	50 Hz
control supply voltage frequency 2 rated value	60 Hz
relative negative tolerance of the control supply voltage frequency	-10 %
relative positive tolerance of the control supply voltage frequency	10 %
control supply voltage 1 at AC at 50 Hz rated value	230 V
control supply voltage 1 at AC at 60 Hz rated value	230 V
relative negative tolerance of the control supply voltage at AC at 50 Hz	-15 %
relative positive tolerance of the control supply voltage at AC at 50 Hz	10 %
relative negative tolerance of the control supply voltage at AC at 60 Hz	-15 %
relative positive tolerance of the control supply voltage at AC at 60 Hz	10 %
display version for fault signal	red

MECHANICAL DATA

Specification	Value
size of engine control device	S6
width	120 mm
height	198 mm
depth	250 mm
fastening method	screw fixing
mounting position	With additional fan: With vertical mounting surface +/- 90° rotatable, with vertical mounting surface +/- 22.5° tiltable to the front and back Without additional fan: With vertical mounting surface +/-10° rotatable, with vertical mounting surface +/- 10° t
required spacing with side-by-side mounting upwards	100 mm
required spacing with side-by-side mounting at the side	5 mm
required spacing with side-by-side mounting down-wards	75 mm
wire length maximum	300 m
number of poles for main current circuit	3

CONNECTIONS/ TERMINALS

Specification	Value
type of electrical connection for main current circuit	busbar connection
type of electrical connection for auxiliary and control circuit	screw-type terminals
number of NC contacts for auxiliary contacts	0
number of NO contacts for auxiliary contacts	2
number of CO contacts for auxiliary contacts	1
type of connectable conductor cross-sections for main contacts for box terminal using the front clamping point finely stranded with core end processing	16 ... 70 mm²
type of connectable conductor cross-sections for main contacts for box terminal using the front clamping point finely stranded without core end processing	16 ... 70 mm²
type of connectable conductor cross-sections for main contacts for box terminal using the front clamping point stranded	16 ... 70 mm²
type of connectable conductor cross-sections for main contacts for box terminal using the back clamping point finely stranded with core end processing	16 ... 70 mm²
type of connectable conductor cross-sections for main contacts for box terminal using the back clamping point finely stranded without core end processing	16 ... 70 mm²
type of connectable conductor cross-sections for main contacts for box terminal using the back clamping point stranded	16 ... 70 mm²
type of connectable conductor cross-sections for main contacts for box terminal using both clamping points finely stranded with core end processing	max. 1x 50 mm² 1x 70 mm²
type of connectable conductor cross-sections for main contacts for box terminal using both clamping points finely stranded without core end processing	max. 1x 50 mm² 1x 70 mm²
type of connectable conductor cross-sections for main contacts for box terminal using both clamping points stranded	max. 2x 70 mm²
type of connectable conductor cross-sections for AWG cables for main contacts for box terminal using the back clamping point	6 ... 2/0
type of connectable conductor cross-sections for AWG cables for main contacts for box terminal using the front clamping point	6 ... 2/0
type of connectable conductor cross-sections for AWG cables for main contacts for box terminal using both clamping points	max. 2x 1/0
type of connectable conductor cross-sections for DIN cable lug for main contacts finely stranded	2x (16 ... 95 mm²)
type of connectable conductor cross-sections for DIN cable lug for main contacts stranded	2x (25 ... 120 mm²)
type of connectable conductor cross-sections for auxiliary contacts solid	2x (0.5 ... 2.5 mm²)
type of connectable conductor cross-sections for auxiliary contacts finely stranded with core end processing	2x (0.5 ... 1.5 mm²)
type of connectable conductor cross-sections for AWG cables for main contacts	4 ... 250 kcmil
type of connectable conductor cross-sections for AWG cables for auxiliary contacts	2x (20 ... 14)
type of connectable conductor cross-sections for AWG cables for auxiliary contacts finely stranded with core end processing	2x (20 ... 16)


AMBIENT CONDITIONS

Specification	Value
installation altitude at height above sea level	5 000 m
environmental category during transport according to IEC 60721	2K2, 2C1, 2S1, 2M2 (max. fall height 0.3 m)
environmental category during storage according to IEC 60721	1K6 (only occasional condensation), 1C2 (no salt mist), 1S2 (sand must not get inside the devices), 1M4
environmental category during operation according to IEC 60721	3K6 (no formation of ice, no condensation), 3C3 (no salt mist), 3S2 (sand must not get into the devices), 3M6
ambient temperature during operation	-25 ... +60 °C
ambient temperature during storage	-40 ... +80 °C
derating temperature	40 °C
protection class IP on the front according to IEC 60529	IP00; IP20 with cover
touch protection on the front according to IEC 60529	finger-safe, for vertical contact from the front with cover

UL/CSA RATINGS

Specification	Value
yielded mechanical performance [hp] for 3-phase AC motor at 220/230 V at standard circuit at 50 °C rated value	50 hp
yielded mechanical performance [hp] for 3-phase AC motor at 460/480 V at standard circuit at 50 °C rated value	100 hp
contact rating of auxiliary contacts according to UL	B300 / R300

DIMENSIONAL DRAWING



WIRING CIRCUIT

