

FAG


53244-MP


Axial deep groove ball bearing


Schaeffler ID: 0392565370000

Axial deep groove ball bearing 532..-MP, single direction, with spherical housing washer, solid brass cage

Technical information









Main Dimensions & Performance Data

| d | 220 mm | Inner diameter shaft washer |
|-----------------|-------------|----------------------------------|
| D | 300 mm | Outer diameter housing washer |
| Т | 65,6 mm | Height |
| C _a | 335.000 N | Basic dynamic load rating, axial |
| C _{0a} | 1.330.000 N | Basic static load rating, axial |
| C _{ua} | 37.500 N | Fatigue load limit, axial |
| n _G | 1.420 1/min | Limiting speed |
| n _{ðr} | 1.690 1/min | Reference speed |
| | 1 g | Weight |

Dimensions

| r _{min} | 2 mm | Minimum chamfer dimension |
|------------------|--------|---------------------------------|
| D ₁ | 224 mm | Inner diameter housing washer |
| d ₁ | 295 mm | Outer diameter shaft washer |
| R | 225 mm | Radius spherical housing washer |
| Α | 118 mm | Distance of the center point |
| T ₁ | 75 mm | Height with seat washer |

Mounting dimensions

| d _{a min} | 268 mm | Minimum diameter shaft shoulder |
|--------------------|--------|--------------------------------------|
| D _{a max} | 260 mm | Maximum diameter of housing shoulder |
| r _{a max} | 2 mm | Maximum filled radius |

Calculation factors

A 9,6 Minimum load factor

Additional information

U244 Seat washer

Temperature range

| T _{min} | -30 °C | Operating temperature min. |
|------------------|--------|----------------------------|
| T _{max} | 200 °C | Operating temperature max. |

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all further information and guidelines for this product. For further information you can use the contact form on our website.

