

TopPage>>Search Result>>5200

Angular Contact Ball Bearings

Bearing No. : **NACHI 5200**

Bearing Type
Clearance
Tolerance Class

 (0.002~0.013)

<p>Dimensions</p> <p>d = 10 0 -0.008</p> <p>D = 30 0 -0.009</p> <p>B = 14.3 0 -0.120</p> <p>r = 0.6~1 (Radial Direction)</p> <p>r = 0.6~2 (Axial Direction)</p>		<p>Dimensions</p> <p>da(min) = 15</p> <p>Da(max) = 25</p> <p>ra(max) = 0.6</p> <p>Mass = 0.05 kg</p>
--	--	--

<p>Basic Dynamic Load Rating Cr : 7,300 N</p> <p>Basic Static Load Rating Cor : 4,000 N</p> <p>Limiting Speed ;</p> <p> Grease Lubrication : 18,000 min⁻¹</p> <p> Oil Lubrication : 24,000 min⁻¹</p>	<table border="0"> <tr> <td></td> <td style="text-align: center;">INNER RING</td> <td style="text-align: center;">OUTER RING</td> </tr> <tr> <td>O.D.Surface Runout with Side :</td> <td style="text-align: center;">-</td> <td style="text-align: center;">-</td> </tr> <tr> <td> Axial Runout with Bore :</td> <td style="text-align: center;">-</td> <td style="text-align: center;">-</td> </tr> <tr> <td> Axial Runout with Raceway :</td> <td style="text-align: center;">-</td> <td style="text-align: center;">-</td> </tr> <tr> <td> Width Variation :</td> <td style="text-align: center;">0.015</td> <td style="text-align: center;">0.015</td> </tr> <tr> <td> Radial Runout :</td> <td style="text-align: center;">0.010</td> <td style="text-align: center;">0.015</td> </tr> </table>		INNER RING	OUTER RING	O.D.Surface Runout with Side :	-	-	Axial Runout with Bore :	-	-	Axial Runout with Raceway :	-	-	Width Variation :	0.015	0.015	Radial Runout :	0.010	0.015
	INNER RING	OUTER RING																	
O.D.Surface Runout with Side :	-	-																	
Axial Runout with Bore :	-	-																	
Axial Runout with Raceway :	-	-																	
Width Variation :	0.015	0.015																	
Radial Runout :	0.010	0.015																	