

TopPage>>Search Result>>5203NR

Angular Contact Ball Bearings

Bearing No. : **NACHI 5203NR**

Bearing Type
Clearance
Tolerance Class

(0.003~0.018)

<p>Dimensions</p> <p>d = 17 0 -0.008</p> <p>D = 40 0 -0.011</p> <p>B = 17.5 0 -0.120</p> <p>r = 0.6~1 (Radial Direction)</p> <p>r = 0.6~2 (Axial Direction)</p> <p>D1(max) = 38.1 a(max) = 2.06 b(max) = 1.35</p> <p>D2(max) = 44.6 f(max) = 1.12</p>			<p>Dimensions</p> <p>da(min) = 22 Da(max) = 35 ra(max) = 0.6 Dx(min) = 45.5 Cy(max) = 2.9 Mass = 0.09 kg</p>
--	--	--	--

Basic Dynamic Load Rating Cr :	15,000 N	INNER RING	OUTER RING
Basic Static Load Rating Cor :	9,250 N	O.D.Surface Runout with Side :	-
Limiting Speed ;		Axial Runout with Bore :	-
Grease Lubrication :	12,000 min ⁻¹	Axial Runout with Raceway :	-
Oil Lubrication :	17,000 min ⁻¹	Width Variation :	0.020 0.020
		Radial Runout :	0.010 0.020