

TopPage>>Search Result>>5203AN


Angular Contact Ball Bearings

Bearing No. : **NACHI 5203AN**

Bearing Type Snap Ring Groove **Clearance** CN(Normal) **Tolerance Class** Normal Class
 (0.003~0.018)

Dimensions

$d = 17$ 0
 -0.008
 $D = 40$ 0
 -0.011
 $B = 17.5$ 0
 -0.120
 $r = 0.6 \sim 1$
 (Radial Direction)
 $r = 0.6 \sim 2$
 (Axial Direction)
 $D1(\max) = 38.1$
 $a(\max) = 2.06$
 $a(\max) = 1.35$



Dimensions
 $da(\min) = 22$
 $Da(\max) = 35$
 $ra(\max) = 0.6$
 $Dx(\min) = 45.5$
 $Cy(\max) = 2.9$
 Mass = 0.09 kg

Basic Dynamic Load Rating Cr : **14,200** N
Basic Static Load Rating Cor : **8,800** N
Limiting Speed ;
 Grease Lubrication : **11,000** min⁻¹
 Oil Lubrication : **15,000** min⁻¹

	INNER RING	OUTER RING
O.D.Surface Runout with Side :		-
Axial Runout with Bore :	-	-
Axial Runout with Raceway :	-	-
Width Variation :	0.020	0.020
Radial Runout :	0.010	0.020