

[TopPage](#)>>[Search Result](#)>>5206ANR

Angular Contact Ball Bearings

Bearing No. : **NACHI 5206ANR**

Bearing Type
Clearance
Tolerance Class

(0.005~0.020)

<p>Dimensions</p> <p>d = 30 0 -0.010</p> <p>D = 62 0 -0.013</p> <p>B = 23.8 0 -0.120</p> <p>r = 1~1.5 (Radial Direction)</p> <p>r = 1~3 (Axial Direction)</p> <p>D1(max) = 59.61</p> <p>a(max) = 3.28</p> <p>b(max) = 1.9</p> <p>D2(max) = 67.7</p> <p>f(max) = 1.7</p>		<p>Dimensions</p> <p>da(min) = 36</p> <p>Da(max) = 56</p> <p>ra(max) = 1</p> <p>Dx(min) = 68.5</p> <p>Cy(max) = 4.7</p> <p>Mass = 0.29 kg</p>
----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	--	-----------------------------------------------------------------------------------------------------------------------------------------------

Basic Dynamic Load Rating Cr :	28,600 N	INNER RING	OUTER RING
Basic Static Load Rating Cor :	20,500 N	O.D.Surface Runout with Side :	-
Limiting Speed ;		Axial Runout with Bore :	-
Grease Lubrication :	7,000 min ⁻¹	Axial Runout with Raceway :	-
Oil Lubrication :	9,500 min ⁻¹	Width Variation :	0.020 0.020
		Radial Runout :	0.013 0.025