

TopPage>>Search Result>>7222CDT

# Angular Contact Ball Bearings

Bearing No. : **NACHI 7222CDT**

■ Bearing Type 
■ Clearance 
■ Tolerance Class

<p>Dimensions</p> <p>d = 110 <sup>0</sup><sub>-0.020</sub></p> <p>D = 200 <sup>0</sup><sub>-0.030</sub></p> <p>B = 38 <sup>0</sup><sub>0.000</sub></p> <p>r = 2.1~4 (Radial Direction)</p> <p>r = 2.1~6.5 (Axial Direction)</p> <p>r1 = 1.1~2 (Radial Direction)</p> <p>r1 = 1.1~3.5 (Axial Direction)</p> <p>a = -1</p>		<p>Dimensions</p> <p>da1(min) = 122</p> <p>da2(min) = 122</p> <p>Da1(max) = 188</p> <p>Da2(max) = 193</p> <p>ra(max) = 2</p> <p>ra1(max) = 1</p> <p>Mass = 9.24 kg</p>
--	--	--

Basic Dynamic Load Rating Cr :	<b>277,000</b> N	INNER RING	OUTER RING
Basic Static Load Rating Cor :	<b>315,000</b> N	O.D.Surface Runout with Side :	-
Limiting Speed ;		Axial Runout with Bore :	-
Grease Lubrication :	<b>4,200</b> min <sup>-1</sup>	Axial Runout with Raceway :	-
Oil Lubrication :	<b>5,700</b> min <sup>-1</sup>	Width Variation :	<b>0.025</b> <b>0.025</b>
		Radial Runout :	<b>0.025</b> <b>0.050</b>