

TopPage>>Search Result>>7236CDT

Angular Contact Ball Bearings

Bearing No. : **NACHI 7236CDT**

■ Bearing Type
■ Clearance
■ Tolerance Class

<p>Dimensions</p> <p>d = 180 ⁰_{-0.025}</p> <p>D = 320 ⁰_{-0.040}</p> <p>B = 52 ⁰_{0.000}</p> <p>r = 4~6.5 (Radial Direction)</p> <p>r = 4~9 (Axial Direction)</p> <p>r1 = 1.5~3 (Radial Direction)</p> <p>r1 = 1.5~5 (Axial Direction)</p> <p>a = 3.3</p>		<p>Dimensions</p> <p>da1(min) = 198</p> <p>da2(min) = 189</p> <p>Da1(max) = 302</p> <p>Da2(max) = 311</p> <p>ra(max) = 3</p> <p>ra1(max) = 1.5</p> <p>Mass = 39.8 kg</p>
---	--	--

<p>Basic Dynamic Load Rating Cr : 500,000 N</p> <p>Basic Static Load Rating Cor : 775,000 N</p> <p>Limiting Speed ;</p> <p style="padding-left: 20px;">Grease Lubrication : 2,600 min⁻¹</p> <p style="padding-left: 20px;">Oil Lubrication : 3,500 min⁻¹</p>	<table border="0"> <tr> <td></td> <td style="text-align: center;">INNER RING</td> <td style="text-align: center;">OUTER RING</td> </tr> <tr> <td>O.D.Surface Runout with Side :</td> <td style="text-align: center;">-</td> <td style="text-align: center;">-</td> </tr> <tr> <td>Axial Runout with Bore :</td> <td style="text-align: center;">-</td> <td style="text-align: center;">-</td> </tr> <tr> <td>Axial Runout with Raceway :</td> <td style="text-align: center;">-</td> <td style="text-align: center;">-</td> </tr> <tr> <td>Width Variation :</td> <td style="text-align: center;">0.030</td> <td style="text-align: center;">0.030</td> </tr> <tr> <td>Radial Runout :</td> <td style="text-align: center;">0.030</td> <td style="text-align: center;">0.070</td> </tr> </table>		INNER RING	OUTER RING	O.D.Surface Runout with Side :	-	-	Axial Runout with Bore :	-	-	Axial Runout with Raceway :	-	-	Width Variation :	0.030	0.030	Radial Runout :	0.030	0.070
	INNER RING	OUTER RING																	
O.D.Surface Runout with Side :	-	-																	
Axial Runout with Bore :	-	-																	
Axial Runout with Raceway :	-	-																	
Width Variation :	0.030	0.030																	
Radial Runout :	0.030	0.070																	