

TopPage>>Search Result>>7303CDT

Angular Contact Ball Bearings

Bearing No. : **NACHI 7303CDT**

■ Bearing Type

■ Clearance

■ Tolerance Class

<p>Dimensions</p> <p>d = 17⁰_{-0.008}</p> <p>D = 47⁰_{-0.011}</p> <p>B = 14⁰_{0.000}</p> <p>r = 1~1.5 (Radial Direction)</p> <p>r = 1~3 (Axial Direction)</p> <p>r1 = 0.6~1 (Radial Direction)</p> <p>r1 = 0.6~2 (Axial Direction)</p> <p>a = -3.2</p>		<p>Dimensions</p> <p>da1(min) = 23</p> <p>da2(min) = 23</p> <p>Da1(max) = 41</p> <p>Da2(max) = 43.4</p> <p>ra(max) = 1</p> <p>ra1(max) = 0.6</p> <p>Mass = 0.24 kg</p>
---	--	--

Basic Dynamic Load Rating Cr :	25,800 N		INNER RING	OUTER RING
Basic Static Load Rating Cor :	16,700 N	O.D.Surface Runout with Side :		-
Limiting Speed ;		Axial Runout with Bore :	-	
Grease Lubrication :	20,000 min ⁻¹	Axial Runout with Raceway :	-	
Oil Lubrication :	27,000 min ⁻¹	Width Variation :	0.020	0.020
		Radial Runout :	0.010	0.020