

TopPage>>Search Result>>7306CDT

Angular Contact Ball Bearings

Bearing No. : **NACHI 7306CDT**

■ Bearing Type
■ Clearance
■ Tolerance Class

<p>Dimensions</p> <p>d = 30⁰_{-0.010}</p> <p>D = 72⁰_{-0.013}</p> <p>B = 19⁰_{0.000}</p> <p>r = 1.1~2 (Radial Direction)</p> <p>r = 1.1~3.5 (Axial Direction)</p> <p>r1 = 0.6~1 (Radial Direction)</p> <p>r1 = 0.6~2 (Axial Direction)</p> <p>a = -3.6</p>		<p>Dimensions</p> <p>da1(min) = 37</p> <p>da2(min) = 37</p> <p>Da1(max) = 65</p> <p>Da2(max) = 67</p> <p>ra(max) = 1</p> <p>ra1(max) = 0.6</p> <p>Mass = 0.72 kg</p>
---	--	--

<p>Basic Dynamic Load Rating Cr : 52,500 N</p> <p>Basic Static Load Rating Cor : 40,500 N</p> <p>Limiting Speed ;</p> <p style="padding-left: 20px;">Grease Lubrication : 13,000 min⁻¹</p> <p style="padding-left: 20px;">Oil Lubrication : 18,000 min⁻¹</p>		<p>INNER RING</p> <p>OUTER RING</p>	
	O.D.Surface Runout with Side :		-
	Axial Runout with Bore :	-	
	Axial Runout with Raceway :	-	
	Width Variation :	0.020	0.020
	Radial Runout :	0.013	0.025