

TopPage>>Search Result>>6010ZENR

# Deep-groove Ball Bearings

Bearing No. : **NACHI 6010ZENR**

**Bearing Type** Snap Ring and Shield  **Clearance** CN(Normal)  **Tolerance Class** Normal Class   
 (0.006~0.023)

<p>Dimensions</p> <p>d = 50 <sup>0</sup><sub>-0.012</sub></p> <p>D = 80 <sup>0</sup><sub>-0.013</sub></p> <p>B = 16 <sup>0</sup><sub>-0.120</sub></p> <p>r = 1~1.5 (Radial Direction)</p> <p>r = 1~3 (Axial Direction)</p> <p>r1 = 0.5~ (Radial Direction)</p> <p>r1 = 0.5~ (Axial Direction)</p> <p>D1 = 76.81</p> <p>a = 2.49</p> <p>D2 = 86.6</p> <p>f = 1.7</p>			<p>Dimensions</p> <p>da(min) = 55</p> <p>Da(max) = 75</p> <p>Dx(min) = 88</p> <p>ra(max) = 1</p> <p>Cy(max) = 3.8</p>
---	--	--	---

Basic Dynamic Load Rating Cr :	<b>21,800</b> N		INNER RING	OUTER RING
Basic Static Load Rating Cor :	<b>16,600</b> N	O.D.Surface Runout with Side :	-	-
Limiting Speed ;		Axial Runout with Bore :	-	-
Grease Lubrication :	<b>8,500</b> min <sup>-1</sup>	Axial Runout with Raceway :	-	-
Oil Lubrication :	<b>10,000</b> min <sup>-1</sup>	Width Variation :	<b>0.020</b>	<b>0.020</b>
		Radial Runout :	<b>0.015</b>	<b>0.025</b>