

# Thrust Ball Bearings

Bearing No. : **NACHI 51109**

■ Bearing Type

■ Clearance

■ Tolerance Class

<p>Dimensions</p> <p>d = 45                    0                               -0.012</p> <p>D = 65                    0                               -0.019</p> <p>T3 = -</p> <p>T4 = -</p> <p>r = 0.6~1.5</p> <p>(Radial Direction and Axial Direction)</p> <p>d1(max) = 65</p> <p>D1(min) = 47</p> <p>D2 = -</p> <p>D3 = -</p> <p>S = -</p> <p>R = -</p> <p>A = -</p>		<p>Dimensions</p> <p>da(min) = 57</p> <p>Da2(max) = -</p> <p>ra(max) = 0.6</p> <p>Mass = - kg</p>
---	--	---

Basic Dynamic Load Rating Ca :	<b>27,800</b> N	INNER RING	OUTER RING
Basic Static Load Rating Coa :	<b>69,000</b> N	O.D.Surface Runout with Side :	-
Limiting Speed ;		Axial Runout with Bore :	-
Grease Lubrication :	<b>3,300</b> min <sup>-1</sup>	Axial Runout with Raceway :	-
Oil Lubrication :	<b>4,900</b> min <sup>-1</sup>	Width Variation :	-
		Radial Runout :	-