

Thrust Ball Bearings

Bearing No. : **NACHI 51116**

■ Bearing Type

■ Clearance

■ Tolerance Class

<p>Dimensions</p> <p>d = 80 0 -0.015</p> <p>D = 105 0 -0.022</p> <p>T3 = -</p> <p>T4 = -</p> <p>r = 1~2.2 (Radial Direction and Axial Direction)</p> <p>d1(max) = 105</p> <p>D1(min) = 82</p> <p>D2 = -</p> <p>D3 = -</p> <p>S = -</p> <p>R = -</p> <p>A = -</p>		<p>Dimensions</p> <p>da(min) = 95</p> <p>Da2(max) = -</p> <p>ra(max) = 1</p> <p>Mass = - kg</p>
---	--	---

<p>Basic Dynamic Load Rating Ca : 44,500 N</p> <p>Basic Static Load Rating Coa : 141,000 N</p> <p>Limiting Speed ;</p> <p style="padding-left: 20px;">Grease Lubrication : 2,200 min⁻¹</p> <p style="padding-left: 20px;">Oil Lubrication : 3,300 min⁻¹</p>	<table border="0"> <tr> <td style="width: 50%;"></td> <td style="text-align: center;">INNER RING</td> <td style="text-align: center;">OUTER RING</td> </tr> <tr> <td>O.D.Surface Runout with Side :</td> <td></td> <td style="text-align: center;">-</td> </tr> <tr> <td>Axial Runout with Bore :</td> <td style="text-align: center;">-</td> <td></td> </tr> <tr> <td>Axial Runout with Raceway :</td> <td style="text-align: center;">-</td> <td></td> </tr> <tr> <td>Width Variation :</td> <td style="text-align: center;">-</td> <td></td> </tr> <tr> <td>Radial Runout :</td> <td style="text-align: center;">-</td> <td></td> </tr> </table>		INNER RING	OUTER RING	O.D.Surface Runout with Side :		-	Axial Runout with Bore :	-		Axial Runout with Raceway :	-		Width Variation :	-		Radial Runout :	-	
	INNER RING	OUTER RING																	
O.D.Surface Runout with Side :		-																	
Axial Runout with Bore :	-																		
Axial Runout with Raceway :	-																		
Width Variation :	-																		
Radial Runout :	-																		