

Thrust Ball Bearings

Bearing No. : **NACHI 51122**

■ Bearing Type

■ Clearance

■ Tolerance Class

<p>Dimensions</p> <p>d = 110 0 -0.020</p> <p>D = 145 0 -0.025</p> <p>T3 = - T4 = - r = 1~2.2 (Radial Direction and Axial Direction)</p> <p>d1(max) = 145 D1(min) = 112 D2 = - D3 = - S = - R = - A = -</p>		<p>Dimensions</p> <p>da(min) = 131 Da2(max) = - ra(max) = 1 Mass = - kg</p>
--	--	---

<p>Basic Dynamic Load Rating Ca : 87,000 N</p> <p>Basic Static Load Rating Coa : 288,000 N</p> <p>Limiting Speed ;</p> <p style="padding-left: 20px;">Grease Lubrication : 1,600 min⁻¹</p> <p style="padding-left: 20px;">Oil Lubrication : 2,400 min⁻¹</p>	<table border="0"> <tr> <td style="width: 50%;"></td> <td style="text-align: center;">INNER RING</td> <td style="text-align: center;">OUTER RING</td> </tr> <tr> <td>O.D.Surface Runout with Side :</td> <td style="text-align: center;">-</td> <td style="text-align: center;">-</td> </tr> <tr> <td>Axial Runout with Bore :</td> <td style="text-align: center;">-</td> <td style="text-align: center;">-</td> </tr> <tr> <td>Axial Runout with Raceway :</td> <td style="text-align: center;">-</td> <td style="text-align: center;">-</td> </tr> <tr> <td>Width Variation :</td> <td style="text-align: center;">-</td> <td style="text-align: center;">-</td> </tr> <tr> <td>Radial Runout :</td> <td style="text-align: center;">-</td> <td style="text-align: center;">-</td> </tr> </table>		INNER RING	OUTER RING	O.D.Surface Runout with Side :	-	-	Axial Runout with Bore :	-	-	Axial Runout with Raceway :	-	-	Width Variation :	-	-	Radial Runout :	-	-
	INNER RING	OUTER RING																	
O.D.Surface Runout with Side :	-	-																	
Axial Runout with Bore :	-	-																	
Axial Runout with Raceway :	-	-																	
Width Variation :	-	-																	
Radial Runout :	-	-																	