

Thrust Ball Bearings

Bearing No. : **NACHI 51126**

■ Bearing Type

■ Clearance

■ Tolerance Class

<p>Dimensions</p> <p>d = 130 0 -0.025</p> <p>D = 170 0 -0.025</p> <p>T3 = -</p> <p>T4 = -</p> <p>r = 1~2.2 (Radial Direction and Axial Direction)</p> <p>d1(max) = 170</p> <p>D1(min) = 132</p> <p>D2 = -</p> <p>D3 = -</p> <p>S = -</p> <p>R = -</p> <p>A = -</p>		<p>Dimensions</p> <p>da(min) = 154</p> <p>Da2(max) = -</p> <p>ra(max) = 1</p> <p>Mass = - kg</p>
--	--	--

<p>Basic Dynamic Load Rating Ca : 104,000 N</p> <p>Basic Static Load Rating Coa : 350,000 N</p> <p>Limiting Speed ;</p> <p style="padding-left: 20px;">Grease Lubrication : 1,300 min⁻¹</p> <p style="padding-left: 20px;">Oil Lubrication : 2,000 min⁻¹</p>	<table border="0"> <tr> <td style="width: 50%;"></td> <td style="text-align: center;">INNER RING</td> <td style="text-align: center;">OUTER RING</td> </tr> <tr> <td>O.D.Surface Runout with Side :</td> <td style="text-align: center;">-</td> <td style="text-align: center;">-</td> </tr> <tr> <td>Axial Runout with Bore :</td> <td style="text-align: center;">-</td> <td style="text-align: center;">-</td> </tr> <tr> <td>Axial Runout with Raceway :</td> <td style="text-align: center;">-</td> <td style="text-align: center;">-</td> </tr> <tr> <td>Width Variation :</td> <td style="text-align: center;">-</td> <td style="text-align: center;">-</td> </tr> <tr> <td>Radial Runout :</td> <td style="text-align: center;">-</td> <td style="text-align: center;">-</td> </tr> </table>		INNER RING	OUTER RING	O.D.Surface Runout with Side :	-	-	Axial Runout with Bore :	-	-	Axial Runout with Raceway :	-	-	Width Variation :	-	-	Radial Runout :	-	-
	INNER RING	OUTER RING																	
O.D.Surface Runout with Side :	-	-																	
Axial Runout with Bore :	-	-																	
Axial Runout with Raceway :	-	-																	
Width Variation :	-	-																	
Radial Runout :	-	-																	