

6008-2Z Deep groove ball bearings

- Popular item

- SKF Explorer

Deep groove ball bearings

Bearing data

[Tolerances,](#)

Normal (metric), P6, P5, Normal (inch),

[Radial internal clearance,](#)

Matched bearing pairs, Stainless steel


$d < 10$ mm, Other bearings

Bearing interfaces

[Seat tolerances for standard conditions,](#)

[Tolerances and resultant fits](#)

Technical specification




DIMENSIONS

d	40 mm	Bore diameter
D	68 mm	Outside diameter
B	15 mm	Width
d_1	≈ 49.25 mm	Shoulder diameter
D_2	≈ 61.1 mm	Recess diameter
$r_{1,2}$	min. 1 mm	Chamfer dimension

ABUTMENT DIMENSIONS

d_c min.	44.6 mm	Diameter of shaft abutment
d_c max.	49.2 mm	Diameter of shaft abutment
D_i max.	63.4 mm	Diameter of housing abutment
r_a max.	1 mm	Radius of shaft or housing fillet



CALCULATION DATA

C	17.8 kN	Basic dynamic load rating
C ₀	11 kN	Basic static load rating
P _u	0.49 kN	Fatigue load limit
	22 000 r/min	Reference speed
	11 000 r/min	Limiting speed
k _r	0.025	Minimum load factor
f ₀	15	Calculation factor

MASS

0.2 kg	Mass bearing
--------	--------------

TOLERANCE CLASS

P6	Dimensional tolerances
P6	Radial run-out