



W 61804-2Z Deep groove ball bearings

- Popular item

Deep groove ball bearings

Bearing data

[Tolerances,](#)

Normal (metric), P6, P5, Normal (inch),

[Radial internal clearance,](#)

Matched bearing pairs, Stainless steel


$d < 10$ mm, Other bearings

Bearing interfaces

[Seat tolerances for standard conditions,](#)

[Tolerances and resultant fits](#)

Technical specification




DIMENSIONS

d	20 mm	Bore diameter
D	32 mm	Outside diameter
B	7 mm	Width
d_2	≈ 22.6 mm	Recess diameter
D_2	≈ 29.52 mm	Recess diameter
$r_{1,2}$	min. 0.3 mm	Chamfer dimension

ABUTMENT DIMENSIONS

d_{ξ} min. 22 mm	Diameter of shaft abutment
d_{ξ} max. 22.5 mm	Diameter of shaft abutment
D_{ξ} max. 30.5 mm	Diameter of housing abutment
r_a max. 0.3 mm	Radius of shaft or housing fillet



CALCULATION DATA

C	3.12 kN	Basic dynamic load rating
C ₀	2.08 kN	Basic static load rating
P _u	0.09 kN	Fatigue load limit
	48 000 r/min	Reference speed
	24 000 r/min	Limiting speed
k _r	0.02	Minimum load factor
f ₀	13.3	Calculation factor

MASS

0.017 kg	Mass bearing
----------	--------------

TOLERANCE CLASS

Normal	Dimensional tolerances
Normal	Radial run-out