



W 61902-2Z Deep groove ball bearings

- Popular item

Deep groove ball bearings

Bearing data

[Tolerances,](#)

Normal (metric), P6, P5, Normal (inch),

[Radial internal clearance,](#)

Matched bearing pairs, Stainless steel


$d < 10$ mm, Other bearings

Bearing interfaces

[Seat tolerances for standard conditions,](#)

[Tolerances and resultant fits](#)

Technical specification




DIMENSIONS

d	15 mm	Bore diameter
D	28 mm	Outside diameter
B	7 mm	Width
d_1	≈ 18.8 mm	Shoulder diameter
d_2	≈ 18.8 mm	Recess diameter
D_2	≈ 25.3 mm	Recess diameter
$r_{1,2}$	min. 0.3 mm	Chamfer dimension

ABUTMENT DIMENSIONS

d_{ϵ} min. 17 mm	Diameter of shaft abutment
d_{ϵ} max. 18.5 mm	Diameter of shaft abutment
D_{ϵ} max. 26 mm	Diameter of housing abutment
r_a max. 0.3 mm	Radius of shaft or housing fillet



CALCULATION DATA

C	3.71 kN	Basic dynamic load rating
C ₀	2.24 kN	Basic static load rating
P _u	0.095 kN	Fatigue load limit
	56 000 r/min	Reference speed
	28 000 r/min	Limiting speed
k _r	0.025	Minimum load factor
f ₀	14.3	Calculation factor

MASS

0.016 kg	Mass bearing
----------	--------------

TOLERANCE CLASS

Normal	Dimensional tolerances
Normal	Radial run-out