



W 6200 Deep groove ball bearings

Deep groove ball bearings

Bearing data

[Tolerances,](#)

Normal (metric), P6, P5, Normal (inch),

[Radial internal clearance,](#)

Matched bearing pairs, Stainless steel


$d < 10$ mm, Other bearings

Bearing interfaces

[Seat tolerances for standard conditions,](#)

[Tolerances and resultant fits](#)

Technical specification




DIMENSIONS

d	10 mm	Bore diameter
D	30 mm	Outside diameter
B	9 mm	Width
d_2	≈ 15.3 mm	Recess diameter
D_2	≈ 25.28 mm	Recess diameter
$r_{1,2}$	min. 0.6 mm	Chamfer dimension

ABUTMENT DIMENSIONS

d_a	min. 14 mm	Diameter of shaft abutment
D_i	max. 26 mm	Diameter of housing abutment
r_a	max. 0.6 mm	Radius of shaft or housing fillet



CALCULATION DATA

C	4.36 kN	Basic dynamic load rating
C ₀	2.32 kN	Basic static load rating
P _u	0.1 kN	Fatigue load limit
	60 000 r/min	Reference speed
	36 000 r/min	Limiting speed
k _r	0.03	Minimum load factor
f ₀	12.9	Calculation factor

MASS

0.029 kg	Mass bearing
----------	--------------

TOLERANCE CLASS

Normal	Dimensional tolerances
Normal	Radial run-out