



W 6206-2Z Deep groove ball bearings

- Popular item

Deep groove ball bearings

Bearing data

[Tolerances,](#)

Normal (metric), P6, P5, Normal (inch),

[Radial internal clearance,](#)

Matched bearing pairs, Stainless steel


$d < 10$ mm, Other bearings

Bearing interfaces

[Seat tolerances for standard conditions,](#)


[Tolerances and resultant fits](#)

Technical specification



DIMENSIONS

d	30 mm	Bore diameter
D	62 mm	Outside diameter
B	16 mm	Width
d_1	≈ 40.7 mm	Shoulder diameter
d_2	≈ 40.7 mm	Recess diameter
D_2	≈ 55.13 mm	Recess diameter
$r_{1,2}$	min. 1 mm	Chamfer dimension



ABUTMENT DIMENSIONS

d_{ϵ} min. 35 mm	Diameter of shaft abutment
d_{ϵ} max. 40.5 mm	Diameter of shaft abutment
D_i max. 57 mm	Diameter of housing abutment
r_a max. 1 mm	Radius of shaft or housing fillet

CALCULATION DATA

C	16.5 kN	Basic dynamic load rating
C ₀	11.2 kN	Basic static load rating
P _u	0.48 kN	Fatigue load limit
	26 000 r/min	Reference speed
	13 000 r/min	Limiting speed
k _r	0.03	Minimum load factor
f ₀	13.9	Calculation factor

MASS

0.2 kg	Mass bearing
--------	--------------

TOLERANCE CLASS

Normal	Dimensional tolerances
Normal	Radial run-out