

NUP 230 ECML

- SKF Explorer

Cylindrical roller bearings, single row

Bearing data

Tolerances,

Normal (metric), P6, Normal (inch),

Radial internal clearance,

cylindrical bore, tapered bore,

Axial internal clearance,


NUP, NJ + HJ

Bearing interfaces

Seat tolerances for standard conditions,

Tolerances and resultant fit

Technical specification



DIMENSIONS

Bore diameter	150 mm	d
Outside diameter	270 mm	D
Width	45 mm	В
Shoulder diameter of inner ring	≈193 mm	d1
Shoulder diameter of outer ring	≈233.2 mm	D1
Chamfer dimension of loose flange ring	182 mm	F
Chamfer dimension	min.3 mm	r1,2
Chamfer dimension of loose flange ring	min.3 mm	r3,4

ABUTMENT DIMENSIONS

	T _a	1	
D _a d _a		d _b	d _b
<u> </u>	VEV		•

da	min.164 mm	Diameter of spacer sleeve
db	min.196 mm	Diameter of shaft abutment
Da	max.254.6 mm	Diameter of housing abutment
ra	max.2.5 mm	Radius of fillet



CALCULATION DATA

Basic dynamic load rating	С	510 kN
Basic static load rating	C_0	600 kN
Fatigue load limit	P_{u}	64 kN
Reference speed		2 600 r/min
Limiting speed		4 500 r/min
Minimum load factor	k _r	0.23
Limiting value	е	0.2
Axial load factor	Υ	0.6

MASS

Mass	12.1 kg
	3

More information

Product details	Engineering information	Tools
Designs and variants	Principles of rolling bearing selection	SimPro Quick
Bearing data	General bearing knowledge	Bearing Select
Loads Temperature limits	Bearing selection process	Engineering Calculator
	Bearing failure and how to	LubeSelect for SKF greases
Permissible speed	prevent it	Heater selection tool
Design considerations		Oil Injection Method Program
Designation system		Rolling bearings mounting and dismounting instructions

