
SKF.



Technical specification




NUP 309 ECJ


- Popular item - SKF Explorer Cylindrical roller bearings, single row

Bearing data Tolerances, Normal (metric), P6, Normal (inch), Radial internal clearance, cylindrical bore, tapered bore, Axial internal clearance, NUP, NJ + HJ Bearing interfaces Seat tolerances for standard conditions, Tolerances and resultant fit

DIMENSIONS

d	45 mm	Bore diameter
D	100 mm	Outside diameter
В	25 mm	Width
d1	≈64.4 mm	Shoulder diameter of inner ring
D1	≈83.2 mm	Shoulder diameter of outer ring
F	58.5 mm	Chamfer dimension of loose flange ring
r1,2	min.1.5 mm	Chamfer dimension
r3,4	min.1.5 mm	Chamfer dimension of loose flange ring





ABUTMENT DIMENSIONS

da	min.54 mm	Diameter of spacer sleeve
db	min.67 mm	Diameter of shaft abutment
Da	max.91.4 mm	Diameter of housing abutment
ra	max.1.5 mm	Radius of fillet



CALCULATION DATA

Basic dynamic load rating	С	112 kN
Basic static load rating	C ₀	100 kN
Fatigue load limit	P _u	12.9 kN
Reference speed		7 500 r/min
Limiting speed		8 500 r/min
Minimum load factor	k _r	0.15
Limiting value	e	0.2
Axial load factor	Y	0.6

MASS

Mass 0.93	kg
-----------	----

More information

Product detailsEngineDesigns and variantsPrincipBearing dataGenerLoadsBearingTemperature limitsBearingPermissible speedPreventDesign considerationsDesignation system

Engineering information

Principles of rolling bearing selection

General bearing knowledge

Bearing selection process

Bearing failure and how to prevent it

Tools

SimPro Quick

Bearing Select

Engineering Calculator

LubeSelect for SKF greases

Heater selection tool

Oil Injection Method Program

Rolling bearings mounting and dismounting instructions



