

81105 TN

- Popular item



Cylindrical roller thrust bearings

Bearing data, Design considerations

[Tolerances,](#)

table, table, values,



[Design considerations,](#)

table

Bearing interfaces

[Seat tolerances for standard conditions](#)

Technical specification



DIMENSIONS

d	25 mm	Bore diameter
D	42 mm	Outside diameter
H	11 mm	Nominal height
d ₁	42 mm	Outside diameter shaft washer
D ₁	26 mm	Bore diameter housing washer
B	3 mm	Height shaft washer
r _{1,2}	min.0.6 mm	Chamfer dimension housing washer

ABUTMENT DIMENSIONS

da	min.41 mm	Abutment diameter shaft
Da	max.26 mm	Abutment diameter housing
ra	max.0.6 mm	Fillet radius

CALCULATION DATA

Basic dynamic load rating	C	25 kN
Basic static load rating	C ₀	69.5 kN
Fatigue load limit	P _u	6.8 kN
Reference speed		3 200 r/min
Limiting speed		6 300 r/min
Minimum axial load factor	A	0

MASS

Mass bearing	0.053 kg
--------------	----------

INCLUDED PRODUCTS

Roller and cage thrust assembly	K 81105 TN
Shaft washer	WS 81105
Housing washer	GS 81105