



AXK 5578

- Popular item

Needle roller thrust bearings

Bearing data, Design considerations

[Tolerances,](#)

table, values,


[Design considerations,](#)

table

Bearing interfaces

[Seat tolerances for standard conditions](#)

Technical specification



DIMENSIONS

d	55 mm	Bore diameter
D	78 mm	Outside diameter
D _w	3 mm	Diameter roller
Ea	min.60 mm	Raceway diameter (min.) roller and cage thrust assembly
Eb	max.76 mm	Raceway diameter (max.) roller and cage thrust assembly

CALCULATION DATA

Basic dynamic load rating	C	34.5 kN
Basic static load rating	C ₀	186 kN
Fatigue load limit	P _u	22.4 kN
Reference speed		2 200 r/min
Limiting speed		4 300 r/min

MASS

Mass roller and cage thrust assembly	0.028 kg
--------------------------------------	----------

ASSOCIATED PRODUCTS

Universal washer	LS 5578
Thin universal washer	AS 5578
Shaft washer	WS 81111
Housing washer	GS 81111

More information

<p>Product details</p> <p>Designs and variants</p> <hr/> <p>Bearing data</p> <hr/> <p>Loads</p> <hr/> <p>Temperature limits</p> <hr/> <p>Permissible speed</p> <hr/> <p>Design considerations</p> <hr/> <p>Designation system</p> <hr/>	<p>Engineering information</p> <p>Principles of rolling bearing selection</p> <hr/> <p>General bearing knowledge</p> <hr/> <p>Bearing selection process</p> <hr/> <p>Bearing failure and how to prevent it</p> <hr/>	<p>Tools</p> <p>SimPro Quick</p> <hr/> <p>Bearing Select</p> <hr/> <p>Engineering Calculator</p> <hr/> <p>LubeSelect for SKF greases</p> <hr/> <p>Heater selection tool</p> <hr/>
---	--	---