


# 51128 Thrust ball bearings, single direction

# Thrust ball bearings, single direction

Bearing data Tolerances, table 1 Bearing interfaces
Seat tolerances for standard conditions,


Tolerances and resultant fit

## Technical specification



#### **DIMENSIONS**

d	140 mm	Bore diameter
D	180 mm	Outside diameter
Н	31 mm	Height
$d_1$	≈ 178 mm	Outside diameter shaft washer
$D_1$	≈ 142 mm	Inner diameter housing washer
r <sub>1,2</sub>	min. 1 mm	Chamfer dimension washer



## **ABUTMENT DIMENSIONS**

d <sub>a</sub> min. 164 mm	Abutment diameter shaft
D <sub>2</sub> max. 156 mm	Abutment diameter housing
r <sub>a</sub> max. 1 mm	Fillet radius





## CALCULATION DATA

Basic dynamic load rating	C 111 kN	С
Basic static load rating	C <sub>0</sub> 440 kN	$C_0$
Fatigue load limit	P <sub>u</sub> 12.9 kN	$P_{u}$
Reference speed	1 800 r/min	
Limiting speed	2 600 r/min	
Minimum load factor	A 1	Α

## MASS

2.05 kg Mass bearing (including seat washer where applicable)

#### More information

Engineering information	Tools
Principles of rolling bearing selection	Bearing Select
General bearing knowledge	Engineering Calculator
Bearing selection process	SimPro Quick
Bearing interfaces	LubeSelect for SKF greases
Seat tolerances for	Heater selection tool
standard conditions	
Lubrication	
External sealing, mounting and dismounting	
Bearing failure and how to prevent it	
	Selection  General bearing knowledge  Bearing selection process  Bearing interfaces  Seat tolerances for standard conditions  Lubrication  External sealing, mounting and dismounting  Bearing failure and how to

