


53214 Thrust ball bearings, single direction


Thrust ball bearings, single direction

Bearing data Tolerances, table 1

Bearing interfaces
Seat tolerances for standard conditions,
Tolerances and resultant fit

Technical specification






DIMENSIONS

d	70 mm	Bore diameter
D	105 mm	Outside diameter
Н	27 mm	Height
H ₁	32 mm	Height bearing including seat washer
d_1	≈ 105 mm	Outside diameter shaft washer
D_1	≈ 72 mm	Inner diameter housing washer
D ₂	88 mm	Inner diameter sphered seat washer
D3	110 mm	Outside diameter sphered housing washer
С	9 mm	Height sphered housing washer
R	80 mm	Radius sphered housing washer
S	38 mm	Centre height housing washer sphere
r _{1,2}	min. 1 mm	Chamfer dimension washer


ABUTMENT DIMENSIONS







d _a min. 91 mm	Abutment diameter shaft
D ₂ max. 88 mm	Abutment diameter housing
r _a max. 1 mm	Fillet radius



CALCULATION DATA

Basic dynamic load rating	C 62.4 kN	С
Basic static load rating	C ₀ 160 kN	C_0
Fatigue load limit	P _u 5.85 kN	P_{u}
Reference speed	2 600 r/min	
Limiting speed	3 600 r/min	
Minimum load factor	A 0.16	Α

MASS

0.97 kg	Mass bearing (including seat washer where applicable)
	· · · · · · · · · · · · · · · · · · ·

ASSOCIATED PRODUCTS



