



3210 A-2Z Angular contact ball bearings, double row

- Popular item
- SKF Explorer

Angular contact ball bearings, double row


Bearing data

[Tolerances](#),
Normal, P6, P5,
[Internal clearance](#),
table, drawing no

Bearing interfaces

[Seat tolerances for standard conditions](#),
[Tolerances and resultant fit](#)

Technical specification




DIMENSIONS

d	50 mm	Bore diameter
D	90 mm	Outside diameter
B	30.2 mm	Width
d ₂	≈ 57.8 mm	Recess diameter inner ring shoulder
D ₂	≈ 82.1 mm	Recess diameter outer ring shoulder
r _{1,2}	min. 1.1 mm	Chamfer dimension inner ring
a	52 mm	Distance pressure point(s)

ABUTMENT DIMENSIONS

d _e	min. 57 mm	Abutment diameter shaft
d _e	max. 57.5 mm	Abutment diameter shaft
D _i	max. 83 mm	Abutment diameter housing
r _a	max. 1 mm	Fillet radius



CALCULATION DATA

C	51 kN	Basic dynamic load rating
C ₀	42.5 kN	Basic static load rating
P _u	1.8 kN	Fatigue load limit
	8 000 r/min	Reference speed
	7 000 r/min	Limiting speed
k _r	0.06	Calculation factor
e	0.8	Calculation factor
X	0.63	Calculation factor
Y ₀	0.66	Calculation factor
Y ₁	0.78	Calculation factor
Y ₂	1.24	Calculation factor

MASS

	0.65 kg	Mass bearing
--	---------	--------------