



7201 BEP Angular contact ball bearings, single row

- Popular item

Angular contact ball bearings, single row

Bearing data

[Tolerances,](#)

Normal (metric), P6, P5, Normal (inch),

[Internal clearance,](#)

CA+CB+CC, G,

[Preload,](#)


GA+GB+GC

Bearing interfaces

[Seat tolerances for standard conditions,](#)

[Tolerances and resultant fit](#)

Technical specification



DIMENSIONS

d	12 mm	Bore diameter
D	32 mm	Outside diameter
B	10 mm	Width
d1	≈ 20.2 mm	Shoulder diameter inner ring (large side face)
d2	≈ 16.57 mm	Shoulder diameter inner ring (small side face)
D1	≈ 25 mm	Shoulder diameter outer ring (large side face)
a	14 mm	Distance pressure point
r _{1,2}	min. 0.6 mm	Chamfer dimension
r _{3,4}	min. 0.3 mm	Chamfer dimension outer ring small side face

ABUTMENT DIMENSIONS

d _e min. 16.2 mm	Abutment diameter shaft
D _i max. 27.8 mm	Abutment diameter housing
D _l max. 30 mm	Abutment diameter housing
r _a max. 0.6 mm	Fillet radius
r _b max. 0.3 mm	Fillet radius



CALCULATION DATA

C	7.61 kN	Basic dynamic load rating
C ₀	3.8 kN	Basic static load rating
P _u	0.16 kN	Fatigue load limit
	28 000 r/min	Reference speed
	26 000 r/min	Limiting speed
A	0	Calculation factor
k _r	0.095	Calculation factor
e	1.14	Calculation factor

SINGLE BEARING OR BEARING PAIR ARRANGED IN TANDEM

X	0.35	Calculation factor
Y ₀	0.26	Calculation factor
Y ₂	0.57	Calculation factor

BEARING PAIR ARRANGED BACK-TO-BACK OR FACE-TO-FACE

X	0.57	Calculation factor
Y ₀	0.52	Calculation factor
Y ₁	0.55	Calculation factor
Y ₂	0.93	Calculation factor