



7248 BCBM Angular contact ball bearings, single row

- Popular item

Angular contact ball bearings, single row

Bearing data

Tolerances,

Normal (metric), P6, P5, Normal (inch),

Internal clearance,

CA+CB+CC, G,

Preload,


GA+GB+GC

Bearing interfaces

Seat tolerances for standard conditions,

Tolerances and resultant fit

Technical specification



DIMENSIONS

d	240 mm	Bore diameter
D	440 mm	Outside diameter
B	72 mm	Width
d1	≈ 322.6 mm	Shoulder diameter inner ring (large side face)
d2	≈ 292.62 mm	Shoulder diameter inner ring (small side face)
D1	≈ 360.41 mm	Shoulder diameter outer ring (large side face)
a	180 mm	Distance pressure point
r _{1,2}	min. 4 mm	Chamfer dimension
r _{3,4}	min. 1.5 mm	Chamfer dimension outer ring small side face

ABUTMENT DIMENSIONS

d _a	min. 257 mm	Abutment diameter shaft
D _c	max. 423 mm	Abutment diameter housing
D _i	max. 431 mm	Abutment diameter housing
r _a	max. 4 mm	Fillet radius
r _b	max. 1.5 mm	Fillet radius



CALCULATION DATA

C	364 kN	Basic dynamic load rating
C ₀	540 kN	Basic static load rating
P _u	12.5 kN	Fatigue load limit
	1 600 r/min	Reference speed
	1 700 r/min	Limiting speed
A	5.12	Calculation factor
k _r	0.08	Calculation factor
e	1.14	Calculation factor

SINGLE BEARING OR BEARING PAIR ARRANGED IN TANDEM

X	0.35	Calculation factor
Y ₀	0.26	Calculation factor
Y ₂	0.57	Calculation factor

BEARING PAIR ARRANGED BACK-TO-BACK OR FACE-TO-FACE

X	0.57	Calculation factor
Y ₀	0.52	Calculation factor
Y ₁	0.55	Calculation factor
Y ₂	0.93	Calculation factor