



QJ 248 N2MA Angular contact ball bearings, four-point contact ball bearings

Angular contact ball bearings, four-point contact ball bearings

Bearing data

[Tolerances](#),

Normal, P6,

[Internal clearance](#),


table

Bearing interfaces

[Seat tolerances for standard conditions](#),

[Tolerances and resultant fit](#)

Technical specification




DIMENSIONS

d	240 mm	Bore diameter
D	440 mm	Outside diameter
B	72 mm	Width
d ₁	≈ 315 mm	Shoulder diameter inner ring
D ₁	≈ 365 mm	Shoulder diameter outer ring/ inner diameter housing washer
a	238 mm	Distance pressure point(s)
h	12.5 mm	Locating slot depth outer ring
b	15 mm	Locating slot width outer ring
r ₀	2.5 mm	Corner radius locating slot
r _{1,2}	min. 4 mm	Chamfer dimension inner ring

ABUTMENT DIMENSIONS

d _a	min. 258 mm	Abutment diameter shaft
D _c	max. 422 mm	Abutment diameter housing
r _a	max. 3 mm	Fillet radius



CALCULATION DATA

C	650 kN	Basic dynamic load rating
C ₀	1 200 kN	Basic static load rating
P _u	27.5 kN	Fatigue load limit
	2 400 r/min	Limiting speed
A	4.27	Calculation factor
e	0.95	Calculation factor
X	0.6	Calculation factor
Y ₀	0.58	Calculation factor
Y ₁	0.66	Calculation factor
Y ₂	1.07	Calculation factor

MASS

	53.2 kg	Mass bearing
--	---------	--------------