



**The Timken Company**  
4500 Mt Pleasant St. NW  
N. Canton, OH 44720

**Phone:** (234) 262-3000

**E-Mail:** [CustomerCAD@timken.com](mailto:CustomerCAD@timken.com) • **Web site:** [www.timken.com](http://www.timken.com)

## Part Number 6007-2RS-NR-C3, Deep Groove Ball Bearings (6000, 6200, 6300, 6400)

Timken's deep groove ball bearings deliver reliable performance in a wide range of applications and conditions. With super-finished raceways and controlled geometries, our premium design helps ensure consistent quality.



[Specifications](#) | [Dimensions](#) | [Basic Load Ratings](#) | [Factors](#)

### Specifications

Clearance	C3
Bore Size d	35.000 mm
Features	Contact Seals With Snap Ring
Bearing Type	Standard DGBB
Weight	0.15 Kg

### Dimensions

Outside Diameter D	62.000 mm
Outside Ring Width B	14.000 mm




Radius Rs min	1.000 mm
Snap Ring Diameter D2 max	67.700 mm
Snap Ring Width f max	1.700 mm

## Basic Load Ratings

Cr - Dynamic Load Rating	15.9 kN
C0r - Static Load Rating	10.3 kN

## Factors

Grease Reference Speed	11000 rpm
Oil Reference Speed	16000 rpm



METRIC UNITS

Weight 0.15 kg

**TIMKEN**®

**THE TIMKEN COMPANY**  
NORTH CANTON, OHIO USA

**6007-2RS-NR-C3**  
Deep Groove Ball Bearings (6000, 6200, 6300, 6400)

Dynamic Load Rating 15900 N  
Static Load Rating 10300 N

Every reasonable effort has been made to ensure the accuracy of the information contained in this writing, but no liability is accepted for errors, omissions or for any other reason.

**FOR DISCUSSION ONLY**