

## **The Timken Company** 4500 Mt Pleasant St. NW


N. Canton, OH 44720 Phone: (234) 262-3000

E-Mail: <u>CustomerCAD@timken.com</u> • Web site: <u>www.timken.com</u>

Part Number 61807-ZZ-C3, Thin Section Ball Bearings (61700, 61800, 61900)

Timken's deep groove ball bearings deliver reliable performance in a wide range of applications and conditions. With super-finished raceways and controlled geometries, our premium design helps ensure consistent quality.





## <u>Specifications</u> | <u>Dimensions</u> | <u>Basic Load Ratings</u> | <u>Factors</u>

Specifications -					
	Clearance	C3			
	Bore Size d	35.000 mm			
	Features	Shields			
	Weight	0.0270 Kg			


Dir	nensions		-
	Outside Diameter D	47.000 mm	
	Outside Ring Width B	7.000 mm	
	adius Rs min	0.300 mm	



Basic Load Ratings –					
Cr - Dynamic Load Rating	4.7 kN				
COr - Static Load Rating	3.8 kN				

Grease Limiting Speed 13000 rpm  Oil Limiting Speed 16000 rpm	Factors		-
Oil Limiting Speed 16000 rpm	Grease Limiting Speed	13000 rpm	
	Oil Limiting Speed	16000 rpm	





**METRIC UNITS** 

Weight 0.027 kg

THE TIMKEN COMPANY NORTH CANTON, OHIO USA

61807-ZZ-C3

Thin Section Ball Bearings (61700, 61800, 61900)

Dynamic Load Rating Static Load Rating 4700 3800

no **r** 

FOR DISCUSSION ONLY

Every reasonable effort has been made to ensure the accuracy of the information contained in this writing, but no liability is accepted for errors, omissions or for any other reason.