


Part Number 61808-C3, Thin Section Ball Bearings (61700, 61800, 61900)

Timken's deep groove ball bearings deliver reliable performance in a wide range of applications and conditions. With super-finished raceways and controlled geometries, our premium design helps ensure consistent quality.





Specifications | Dimensions | Basic Load Ratings | Factors

| Specifications – | | | | | | | |
|------------------|----------------------|-----------|--|--|--|--|--|
| | Clearance | C3 | | | | | |
| | Bore Size d | 40.000 mm | | | | | |
| | Features | Open | | | | | |
| | Weight | 0.029 Kg | | | | | |
| | | | | | | | |
| Dimensions – | | | | | | | |
| | Outside Diameter D | 52.000 mm | | | | | |
| 6 | Outside Ring Width B | 7.000 mm | | | | | |
| | adius Rs min | 0.300 mm | | | | | |
| | | | فروشگاه کالا مىنعتى www.kalasanati.com کال مىنعتى تنها يک فروشکاه نيست! آموزش، انتخاب، خريد | | | | |

| Basic Load Ratings | | | | | - | | |
|--------------------|-----------|-----------|--|--|---|--|--|
| Cr - Dynamic Lo | ad Rating | 4.9 kN | | | | | |
| COr - Static Load | I Rating | 4.2 kN | | | | | |
| Factors - | | | | | | | |
| Grease Limiting | Speed | 12000 rpm | | | | | |
| Oil Limiting Spe | ed | 14000 rpm | | | | | |



