

The Timken Company 4500 Mt Pleasant St. NW N. Canton, OH 44720 Phone: (234) 262-3000

E-Mail: <u>CustomerCAD@timken.com</u> • Web site: <u>www.timken.com</u>

Part Number 6216-RS-C3, Deep Groove Ball Bearings (6000, 6200, 6300, 6400)

Timken's deep groove ball bearings deliver reliable performance in a wide range of applications and conditions. With super-finished raceways and controlled geometries, our premium design helps ensure consistent quality.



<u>Specifications</u> | <u>Dimensions</u> | <u>Basic Load Ratings</u> | <u>Factors</u>

Specifications –				
	Clearance	C3		
	Bore Size d	80.000 mm		
	Features	One Contact Seal		
	Bearing Type	Standard DGBB		
	Weight	1.4 Kg		

Dimensions		-)
Outside Diameter D	140.000 mm	
utside Ring Width B	26.000 mm	




Radius Rs min	2.000 mm
---------------	----------

Cr - Dynamic Load Rating 72.7 kN C0r - Static Load Rating 53 kN	Bas	sic Load Ratings	-
COr - Static Load Rating 53 kN		Cr - Dynamic Load Rating	72.7 kN
		COr - Static Load Rating	53 kN

Factors		-
Grease Reference Speed	5200 rpm	
Oil Reference Speed	7500 rpm	





METRIC UNITS

Weight 1.4 kg

THE TIMKEN COMPANY
NORTH CANTON, OHIO USA

6216-RS-C3

Deep Groove Ball Bearings (6000, 6200, 6300, 6400)

Dynamic Load Rating Static Load Rating 72700 53000

Ν

1 20

FOR DISCUSSION ONLY

Every reasonable effort has been made to ensure the accuracy of the information contained in this writing, but no liability is accepted for errors, omissions or for any other reason.