

**TIMKEN****The Timken Company**


4500 Mt Pleasant St. NW

N. Canton, OH 44720

**Phone:** (234) 262-3000**E-Mail:** [CustomerCAD@timken.com](mailto:CustomerCAD@timken.com) • **Web site:** [www.timken.com](http://www.timken.com)

Part Number 7216 BM/CN, Timken® Single Row Angular Contact Ball Bearings (7200, 7300)

Timken® angular contact ball bearings are designed for combination radial and axial loading. Single-row bearings have high thrust capacity in one direction. Some single-row bearings are specifically designed for duplex mounting in sets for maximum performance.



[Dimensions](#) | [Basic Load Ratings](#) | [Factors](#) | [Specifications](#) | [Abutment and Fillet Dimensions](#)

### Dimensions

<b>d - Bore</b>	80.00 mm 3.1496 in
<b>D - Outer Diameter</b>	140.00 mm 5.5118 in
<b>Bearing Width</b>	26.00 mm 1.0236 in
<b>Contact Angle</b>	40 °

### Basic Load Ratings



**C0 - Static Radial Rating**

69500 N  
15621 lbf

<b>C1 ISO - Dynamic Radial Rating</b>	80500 N 18093 lbf
---------------------------------------	----------------------

## Factors

<b>Limiting Speed (Grease)</b>	4300 rpm
<b>Limiting Speed (Oil)</b>	5700 rpm

## Specifications

<b>Ball Type</b>	STEEL
<b>Cage Type</b>	Machined
<b>Cage Material</b>	Brass
<b>Bearing Weight</b>	1.63 Kg 3.594 lb
<b>Design Units</b>	METRIC
<b>R - Inner Ring "Touch" Radius</b>	0.6
<b>r - Outer Ring "Touch" Radius</b>	0.6
<b>Features</b>	Open


## Abutment and Fillet Dimensions

<b>R - Inner Ring "To Clear" Radius<sup>1</sup></b>	1.00 mm 0.039 in
<b>r - Outer Ring "To Clear" Radius<sup>2</sup></b>	1.00 mm 0.039 in
<b>da - Inner Ring Backing Diameter</b>	90.0 mm 3.543 in
<b>Da - Outer Ring Backing</b>	130.00 mm

**Diameter**

5.1180 in

- <sup>1</sup> Maximum housing fillet radius that bearing corners will clear.
- <sup>2</sup> Maximum shaft fillet radius that bearing corners will clear.



METRIC UNITS

Number of Balls Per Row 16  
 Bearing Weight 1.630 kg

**TIMKEN**®

**7216 BM/CN**  
 Timken® Single Row Angular Contact Ball Bearings  
 (7200, 7300)

**THE TIMKEN COMPANY**  
 NORTH CANTON, OHIO USA

Dynamic Radial Rating 80500 N  
 Static Radial Rating 69500 N

Every reasonable effort has been made to ensure the accuracy of the information contained in this writing, but no liability is accepted for errors, omissions or for any other reason.

**FOR DISCUSSION ONLY**