



**The Timken Company**

4500 Mt Pleasant St. NW


N. Canton, OH 44720

Phone: (234) 262-3000

E-Mail: [CustomerCAD@timken.com](mailto:CustomerCAD@timken.com) • Web site: [www.timken.com](http://www.timken.com)

## Part Number 7226 BM/CN, Timken® Single Row Angular Contact Ball Bearings (7200, 7300)

Timken® angular contact ball bearings are designed for combination radial and axial loading. Single-row bearings have high thrust capacity in one direction. Some single-row bearings are specifically designed for duplex mounting in sets for maximum performance.



[Dimensions](#) | [Basic Load Ratings](#) | [Factors](#) | [Specifications](#) | [Abutment and Fillet Dimensions](#)

### Dimensions

<b>d - Bore</b>	130.00 mm 5.1181 in
<b>D - Outer Diameter</b>	230.00 mm 9.0551 in
<b>Bearing Width</b>	40.00 mm 1.5748 in
<b>Contact Angle</b>	40 °

### Basic Load Ratings



**C0 - Static Radial Rating**

174000 N  
39109 lbf

C1 ISO - Dynamic Radial Rating	171000 N 38435 lbf
--------------------------------	-----------------------

## Factors

Limiting Speed (Grease)	2500 rpm
-------------------------	----------

Limiting Speed (Oil)	3400 rpm
----------------------	----------

## Specifications

Ball Type	STEEL
-----------	-------

Cage Type	Machined
-----------	----------

Cage Material	Brass
---------------	-------

Bearing Weight	7.15 Kg 15.765 lb
----------------	----------------------

Design Units	METRIC
--------------	--------

R - Inner Ring "Touch" Radius	0.6
-------------------------------	-----

r - Outer Ring "Touch" Radius	0.6
-------------------------------	-----

Features	Open
----------	------

## Abutment and Fillet Dimensions

R - Inner Ring "To Clear" Radius <sup>1</sup>	1.10 mm 0.043 in
---	---------------------

r - Outer Ring "To Clear" Radius <sup>2</sup>	1.10 mm 0.043 in
---	---------------------


da - Inner Ring Backing Diameter	144.0 mm 5.669 in
----------------------------------	----------------------

Da - Outer Ring Backing	216.0 mm
-------------------------	----------

**Diameter**

8.504 in

- <sup>1</sup> Maximum housing fillet radius that bearing corners will clear.
- <sup>2</sup> Maximum shaft fillet radius that bearing corners will clear.



## METRIC UNITS

Number of Balls Per Row  
Bearing Weight

16  
7.150 kg

**TIMKEN**®

**THE TIMKEN COMPANY**  
NORTH CANTON, OHIO USA

**7226 BM/CN**  
Timken® Single Row Angular Contact Ball Bearings  
(7200, 7300)

Dynamic Radial Rating 171000 N  
Static Radial Rating 174000 N

Every reasonable effort has been made to ensure the accuracy of the information contained in this writing, but no liability is accepted for errors, omissions or for any other reason.

**FOR DISCUSSION ONLY**