

The Timken Company 4500 Mt Pleasant St. NW N. Canton, OH 44720


Phone: (234) 262-3000

E-Mail: <u>CustomerCAD@timken.com</u> • Web site: <u>www.timken.com</u>

Part Number 7305 BTN1, Timken® Single Row Angular Contact Ball Bearings (7200, 7300)

Timken® angular contact ball bearings are designed for combination radial and axial loading. Single-row bearings have high thrust capacity in one direction. Some single-row bearings are specifically designed for duplex mounting in sets for maximum performance.





<u>Dimensions</u> | <u>Basic Load Ratings</u> | <u>Factors</u> | <u>Specifications</u> | <u>Abutment and Fillet Dimensions</u>

Dimensions –			
	d - Bore	25.00 mm 0.9843 in	
	D - Outer Diameter	62.00 mm 2.4409 in	
	Bearing Width	17.00 mm 0.6693 in	
	Contact Angle	40 °	

Basic Load Ratings			-
0 - Static Radial Rating	14100 N 3169 lbf		
	24400 NI	ف من گام کالل مینون	




C1 ISO - Dynamic Radial Rating 5484 lbf

Limiting Speed (Grease) 11000 rpm	
Limiting Speed (Oil) 15000 rpm	

Specifications -			
	Ball Type	STEEL	
	Cage Type	Molded	
	Cage Material	Polyamide	
	Bearing Weight	0.23 Kg 0.507 lb	
	Design Units	METRIC	
	R - Inner Ring "Touch" Radius	0.6	
	r - Outer Ring "Touch" Radius	0.6	
	Features	Open	

Abutment and Fillet Dimensions –				
	R - Inner Ring "To Clear" Radius ¹	0.60 mm 0.024 in		
	r - Outer Ring "To Clear" Radius ²	0.60 mm 0.024 in		
	da - Inner Ring Backing Diameter	32.0 mm 1.260 in		
	Da - Outer Ring Backing Diameter	55.0 mm 2.165 in		





NORTH CANTON, OHIO USA

METRIC UNITS

Number of Balls Per Row 10 Bearing Weight 0.230 kg THE TIMKEN COMPANY

7305 BTN1

Timken® Single Row Angular Contact Ball Bearings (7200, 7300)

Dynamic Radial Rating

24400 14100 Ν

Static Radial Rating

Every reasonable effort has been made to ensure the accuracy of the information contained in this writing, but no liability is accepted for errors, omissions or for any other reason.

FOR DISCUSSION ONLY