

**TIMKEN****The Timken Company**


4500 Mt Pleasant St. NW

N. Canton, OH 44720

**Phone:** (234) 262-3000**E-Mail:** [CustomerCAD@timken.com](mailto:CustomerCAD@timken.com) • **Web site:** [www.timken.com](http://www.timken.com)

Part Number 7308 BTN1/CN, Timken® Single Row Angular Contact Ball Bearings (7200, 7300)

Timken® angular contact ball bearings are designed for combination radial and axial loading. Single-row bearings have high thrust capacity in one direction. Some single-row bearings are specifically designed for duplex mounting in sets for maximum performance.



[Dimensions](#) | [Basic Load Ratings](#) | [Factors](#) | [Specifications](#) | [Abutment and Fillet Dimensions](#)

### Dimensions

<b>d - Bore</b>	40.00 mm 1.5748 in
<b>D - Outer Diameter</b>	90.00 mm 3.5433 in
<b>Bearing Width</b>	23.00 mm 0.9055 in
<b>Contact Angle</b>	40 °

### Basic Load Ratings



**C0 - Static Radial Rating**

27700 N  
6226 lbf

<b>C1 ISO - Dynamic Radial Rating</b>	42200 N 9485 lbf
---------------------------------------	---------------------

## Factors

<b>Limiting Speed (Grease)</b>	7400 rpm
<b>Limiting Speed (Oil)</b>	9900 rpm

## Specifications

<b>Ball Type</b>	STEEL
<b>Cage Type</b>	Molded
<b>Cage Material</b>	Polyamide
<b>Bearing Weight</b>	0.64 Kg 1.411 lb
<b>Design Units</b>	METRIC
<b>R - Inner Ring "Touch" Radius</b>	0.6
<b>r - Outer Ring "Touch" Radius</b>	0.6
<b>Features</b>	Open


## Abutment and Fillet Dimensions

<b>R - Inner Ring "To Clear" Radius<sup>1</sup></b>	1.00 mm 0.039 in
<b>r - Outer Ring "To Clear" Radius<sup>2</sup></b>	1.00 mm 0.039 in
<b>da - Inner Ring Backing Diameter</b>	48.5 mm 1.909 in
<b>Da - Outer Ring Backing</b>	81.5 mm

**Diameter**

3.209 in

- <sup>1</sup> Maximum housing fillet radius that bearing corners will clear.
- <sup>2</sup> Maximum shaft fillet radius that bearing corners will clear.



METRIC UNITS

Number of Balls Per Row	11
Bearing Weight	0.640 kg

**TIMKEN**®

**THE TIMKEN COMPANY**  
NORTH CANTON, OHIO USA

<b>7308 BTN1/CN</b>	
Timken® Single Row Angular Contact Ball Bearings (7200, 7300)	
Dynamic Radial Rating	42200 N
Static Radial Rating	27700 N

Every reasonable effort has been made to ensure the accuracy of the information contained in this writing, but no liability is accepted for errors, omissions or for any other reason.

**FOR DISCUSSION ONLY**