



VD*-W*


CHECK VALVES

SERIES 30

p max **400** bar


Q max (see table of performances)

PRESSURE DROPS Δp -Q



- Add the cracking pressure to the values shown in the diagram.
- Curves measured using mineral oil with viscosity of 36 cSt at 50°C.

OPERATING PRINCIPLE




- VD*-W* valves are check valves with threaded "BSP" ports for mounting in-line on hydraulic lines.
- They allow the flow to pass freely in one direction, blocking it in the opposite direction.
- In rest conditions, the valve poppet is kept closed by a spring. The poppet opens when the pressure in the intake line "A" exceeds the set value of the spring, added to any pressure in the outlet line "B".
- Available in eight sizes for flow rates of up to 850 l/min and with five different cracking pressures.

PERFORMANCES

Valve	BSP port dimension	Maximum flow rate [l/min]	Mass [kg]	Max operating pressure [bar]
VD2-W*	1/4"	25	0,17	400
VD3-W*	3/8"	40	0,26	
VD4-W*	1/2"	75	0,41	
VD5-W*	3/4"	125	0,6	
VD6-W*	1"	200	1,2	320
VD7-W*	1 1/4"	280	1,8	
VD8-W*	1 1/2"	650	3,2	
VD9-W*	2"	850	4,8	

Ambient temperature range	°C	-20 / +60
Fluid temperature range	°C	-20 / +80
Fluid viscosity range	cSt	10 ÷ 400
Fluid contamination degree	cSt	25
Recommended viscosity	acc. to ISO 4406:1999 class 20/18/15	

HYDRAULIC SYMBOL





1 - IDENTIFICATION CODE

V	D		-	W		/	30
---	---	--	---	---	--	---	----

Check valve _____

Nominal dimension _____

2 = 1/4"
3 = 3/8"
4 = 1/2"
5 = 3/4"
6 = 1"
7 = 1 1/4"
8 = 1 1/2"
9 = 2"

Series No.: (The overall and mounting dimensions remain unchanged from 30 to 39)

Cracking pressure: 1 = 0,35 bar
2 = 2 bar
T4 = 4 bar
3 = 6 bar
4 = 10 bar

BSP threaded ports

2 - HYDRAULIC FLUIDS

Use mineral oil-based hydraulic fluids HL or HM type, according to ISO 6743-4.

Using fluids at temperatures higher than 80 °C causes a faster degradation of the fluid and of the seals characteristics.

The fluid must be preserved in its physical and chemical characteristics.

3 - OVERALL AND MOUNTING DIMENSIONS

dimensions in mm

Valve	A BSP	B	C	D
VD2-W*	1/4"	12,5	63	22
VD3-W*	3/8"	12,5	69	27
VD4-W*	1/2"	15,5	80,5	32
VD5-W*	3/4"	17	99,5	36
VD6-W*	1"	20	117	46
VD7-W*	1 1/4"	22	134,5	55
VD8-W*	1 1/2"	24	159	65
VD9-W*	2"	31	198	75