PORTABLE WATER QUALITY METER SMART 987AX SERIES

Electrode integrated with Temperature sensor

Packing example







Compatible with any brands BNC electrodes 10K NTC on the market















- Smart water quality measurement with single input or temperature sensor plug.
- Cost effective with deluxe blow carrying case, portable around and convenient storage.
- Professional look design accurate portable meters with large LCD display, BNC connector.
- Hold function, battery capacity indicator, automatic power off in 15 minutes and may disable.
- Built-in 10K ohm automatic temperature compensation
- Automatically / Manually temperature adjustment by pressing buttons to get accurate reading
- RFS(Recover to Factory Setting) function is included. pH 4.10 slope check electrode aging.
- pH 3 calibration points: 4.01, 7, 10.01 (Adjustable).
- Conductivity calibration point: 1413uS/cm(K=1) or 12.88mnS/cm(K=10). Calibration buffer solution is included.
- Conductivity electrode may convert to TDS and Salinity readings, conversion factor from 0.4 to 1.0.
 Conductivity cell constant (K) selectable: 0.1(Super clean water), 1.0(Fresh water), 10(Sea water). (Selectable)
- DO calibration 100% air calibration and zero calibration without electrode

Compatible DO sensor types (Galvanic or Polarographic, choose one when ordered) type with 3M cable, membrane cap,

electrolyte.

 Manually Salinity (0~50ppt) and Pressure(300~1100hpa)compensation

for DO measurement STANDARD PACKING SUPPLIED:

Complete kit:

Meter, electrode, batteries AAA x3 pcs,manual,carrying case.Calibration buffer(ORP excluded), soaking buffer(Cond.excluded).

 987A0: Meter only in a plan white box. AAA batteries.

P/N	SMART complete set combination models			
987A2_PC	Meter with pH/ Conductivity/TDS/Salt/EC/Temp. in one			
987A2_PO	Meter with pH/ ORP/Temp. in one			
987A2_PD	Meter with pH/ DO/Temp. in one			
987A3_PCD	Meter with pH/ Conductivity/TDS/Salt/EC/DO/Temp. in one			
987A3_PCO	Meter with pH/ Conductivity/TDS/Salt/EC/ORP/Temp. in one			
987A4_PCOD	Meter with pH/ Conductivity/TDS/Salt/EC/ORP/DO/Temp. in one			

Choose electrodes	Models	Electrode body	Temp. Spec.	Sensor type
pH electrode	9 9 716G	PC	N/A	Glass bulb
	9 9 716GT	PC	ATC(NTC10KΩ)	Glass bulb
	9 9 716AT	Epoxy	ATC(NTC10KΩ)	Flat tip
Conductivity electrode	9 9 717G	Glass	K=1. N/A	Platinum disc
	9 9 717A	ABS	K=1. N/A	Graphite plate
	9 9 717GT	Glass	K=1/10 ATC(NTC10 K Ω)	Platinum disc
	9 9 717AT	ABS	K=1/10 ATC(NTC10 K Ω)	Graphite plate
ORP electrode	9 9 718PP	PC	N/A	Platinum pin
	9 9 718PB	Glass	N/A	Platinum band
DO electrode	9 9 719GT	ABS	ATC (NTC10KΩ)	Galvanic
	9 9 719PT	ABS	ATC(NTC10KΩ)	Polarographic