



ENGINEERING INFORMATION

TYPE 1561A			CAPACITY										
			m ³ /h	205	190	175	155	135	115	92			
KW	11	OUTLET 6 in	l/s	57	52.8	49	43	37.5	32	26			
			HEIGHT										
R.P.M	1450	weight 295 kg	m	9	10	11	12	13	14	15			

TYPE 1561B			CAPACITY											
			m3/h	130	122	113	103	90	75	62	48	35	20	5
KW	11	OUTLET 6 in	l/s	36.1	34	31.4	29	25	21	17.2	13.3	9.7	5.6	1.4
HP	15	PIPE DN 150	HEIGHT											
R.P.M	1450	weight 295 kg	m	17.8	19	20	21	22	23	24	25	26	27	28

TYPE 1562A			CAPACITY											
			m3/h	360	330	310	290	270	250	225	200	175	150	90
KW	11	OUTLET 6 in	l/s	100.1	91.7	86.2	80.6	75	69.5	62.5	55.6	48.7	41.7	25
HP	15	PIPE DN 150	HEIGHT											
R.P.M	1450	weight 295 kg	m	3	5	6	7	8	9	10	11	12	13	15

TYPE 1562B			CAPACITY											
			m3/h	165	160	140	120	100	75	45	10	5		
KW	11	OUTLET 6 in	l/s	45.9	44.5	38.9	33.4	27.8	21	12.5	2.8	1.4		
HP	15	PIPE DN 150	HEIGHT											
R.P.M	1450	weight 295 kg	m	15.5	16	17	18	19	20	21	22	22		

IP68 - CLASS F – 380/660 V (Y/Δ) - 24 A - 50HZ

