




Installation Sketch

up to 7.5 kW included






PN16 FLANGES

DN	D	M	G	HOLES		MAX. THICKNESS
				N°	Ø	
80	200	160	138	8	18	22
100	220	180	158	8	18	22



MODEL	DNM	DNA	a	w	x	h2	B1	c	h1	m	m1	n	n1	s	B	H	L	K	
32-125/7	32	50	80	223	113	140	48	12	112	100	70	190	140	15	192	281	427	85	
32-125/11				231	123	160	50	16	132			240	190	14	240	321	430	95	
32-160/15												266	141	496					
32-160/22				258	127	180	48	12	160			240	190	15	248	369	490		
32-160/30			155	264	180	198	60	15	160	272	212	308	386		610	60			
32-200/30										640									
32-200/40																			
32-250/55																			
32-250/75																			
40-125/11	40	65	80	255	127	140	45	12	112	100	70	210	160	15	218	282	489	95	
40-125/15				238	127	168	48		132			240	190		249	330	494	105	
40-125/22												264	212		275	370	553		583
40-160/30				100	259	180	180		50			160	240		190	243	322		518
40-160/40			264					212		272	370		556	586					
40-200/55																			
40-200/75																			
50-125/22			50	65	100	262	127	160	50	12	132	100	70	240	190		243	322	518
50-125/30	262	180				180	52	160	264		212			272	370		556	586	
50-125/40																			
50-160/55	100	265				180	180	68	14		160			125	95		280	212	283
50-160/75																			
65-125/40																			
65-125/55																			
65-125/75	65	80			100	265	180	180	68	14	160	125	95	280	212		283	372	564



MODEL	DNM	DNA	a	w	x	h2	B1	C	C1	h1	m	m1	n	n1	s	B	H	L	K								
40-250/92	40	65	100	310	260	225	65	20	20	180	260	210	320	254		350	440	845	110								
40-250/110																											
40-250/150																											
50-200/92	50	65	100	310	260	200	65	20	-	160	260	210	320	254	14.5	350	420	845	120								
50-200/110									20								180	304	254	440	895	110					
50-250/150						225				70													25	-	311	241	355
50-250/185																											
50-250/220																											
65-160/92	65	80	100	310	260	200	65	20	-	160	260	210	320	254	14.5	350	420	845	125								
65-160/110									20								180	304		254	440	895					
65-160/150																								225	70	22	-
65-200/150						20	180	304	254	440	895																
65-200/185													225	70		22	-	311		241	355	279	455	925			
65-200/220				20	180	304	254	440	920																		
65-200K/185											22	25	369	305	395	318	18.5	505	1020								
65-200K/220				70	22	311	241	355	279	14.5										455	956						
65-200K/300											250	25	200	369	305	395	318	18.5	400			505	1026				
65-250/220				200	369	305	395	318	18.5	400										505	1026						
65-250/300											200	369	305	395	318	18.5	400	505	1026								
65-250/370				200	369	305	395	318	18.5	400										505	1026						
80-160/110											80	100	125	315	260	225	65	20	-			160	260	210	320	254	14.5
80-160/150				22	180	311	241	355	279	355									461	978							
80-160/185																250					70						
80-200/220	280	75	28	225	404	311	435	356	18.5	450				555	1098		120										
80-200/300																80		30	30	280	450	349	490	406	24	550	
80-250/370																											
80-250/450																											
80-250/550																											


Technical Data

PUMP TYPE	POWER		l/min m³/h	Q=DELIVERY																									
	kW	HP		0	100	150	250	300	400	450	600	700	800	900	1200	1400	1500	1800	2000	2300	3000	3500							
32-125/07★	0.75	1	H(m)	17.5	16.7	15	12	9																					
32-125/11★	1.1	1.5		22	21	19.7	16.5	14.5	9																				
32-160/15★	1.5	2		25.4	23.7	22.5	18.5	15.8																					
32-160/22★	2.2	3		31	29.6	28.5	24.5	22	15																				
32-160/30★	3	4		35	34.3	34	28	25.5	19	15																			
32-200/30★	3	4		44.2	43	39.8	35.2	32.2	24.6	19.8																			
32-200/40★	4	5.5		54.5	52	50	45.5	41.9	35	30.3																			
32-250/55★	5.5	7.5		79.5	74.7	71.8	63	56	37.5																				
32-250/75★	7.5	10		99.5	95	91.8	83	76	57.8																				
40-125/11	1.1	1.5		14.7				13.5	11.5	10.1	5.8																		
40-125/15	1.5	2		18.1				17	15	13.9	9.6	6																	
40-125/22	2.2	3		24.5				23.2	21.5	20.2	16	13	8.3																
40-160/30	3	4		31.8				29.5	27.5	26.3	21.5	17.5																	
40-160/40	4	5.5		38				36	34	33	28.5	25	20.1																
40-200/55★	5.5	7.5		46				43.8	41.3	40.1	35	30																	
40-200/75★	7.5	10		57				53.6	51.5	50	45	41	36.5																
40-250/92★	9.2	12.5		64				59	56.5	55	49.5	45	39.8																
40-250/110★	11	15		72				67.5	65	63.5	57.5	52.2	47																
40-250/150★	15	20		84.5				80	77.3	75.2	71	65	61																
50-125/22	2.2	3		17							15.4	14	12.8	11.5	6.5														
50-125/30	3	4		20							18.8	18	17	15.6	11														
50-125/40	4	5.5		24							23.1	23	21.5	20.3	15.8	11.8													
50-160/55	5.5	7.5		32							30.6	30	28	26.6	20.5	14.8													
50-160/75	7.5	10		40							38	37	36	34.4	29	24	21												
50-200/92★	9.2	12.5		50.5							46.8	45	43	40.9	32.5	25.7													
50-200/110★	11	15		57.5							53.5	52	50	47.5	40	33	29												
50-250/150★	15	20		68.5							64	63	61.5	59	50	41													
50-250/185★	18.5	25		77							73.2	72	70	68	60.5	51.5	47												
50-250/220★	22	30		86.3							83	81.5	80.8	78.7	70	61.9	57												
65-125/40	4	5.5		19									17.3	16.8	14.5	13	11.8												
65-125/55	5.5	7.5		23									21.3	20.9	19	17.5	16.7	13.7											
65-125/75	7.5	10		27									26	25.6	24.5	23	22.5	20	18										
65-160/92	9.2	12.5	33										31.5	30	28	27.1	24	21.5											
65-160/110	11	15	36										34.5	33	31.5	30.8	28	25.5											
65-160/150	15	20	42										41	40	38.5	37.8	35	33	29.5										
65-200/150	15	20	45.5										46	43.5	41	39.2	33												
65-200/185	18.5	25	53										53.5	51.2	48.3	47	41.5												
65-200/220	22	30	59										59.5	57.2	54	53	47	43.5											
65-200K/185	18.5	25	41.2										42	41.2	40.6	38.2	36.5	34											
65-200K/220	22	30	48												48	47.5	46	44	41										
65-200K/300	30	40	59.5												59	58.5	58	56.2	54										
65-250/220	22	30	62												61.5	58.2	56.5	54	49	45									
65-250/300	30	40	76												75	73	71.5	69.5	64.5	61.5	54								
65-250/370	37	50	90												88.3	86.5	84	83	78	75	68								
80-160/110	11	15	27												27.3	26	24.5	22.5											
80-160/150	15	20	32.8														32.5	31.3	30.2	28.5									
80-160/185	18.5	25	39														38	36.8	36.7	33.8									
80-200/220	22	30	48														47.5	45.5	43.5	41									
80-200/300	30	45	60														59.5	58	57	54.5									
80-250/370	37	50	71.5														70.5	67.5	65.5	61.5									
80-250/450	45	61	80														80.5	78.5	76.5	73.4									
80-250/550	55	75	92.5														93.5	91.2	89.8	86.8									

★= Stainless steel impeller

Characteristic Curves

XST	~2900rpm	ISO 9906 Annex A
-----	----------	------------------



Hydraulic Performance Curves

XST80-160

~2900rpm

ISO 9906 Annex A

