



MLFB-Ordering data: 1LE1002-1CB23-4AA4

Motor type: 1AV1132B

Client order no.:

Item no.:

Order no.:

Consignment no.:

Offer no.:

Project:

Remarks:

U [V]	Δ/Y	f [Hz]	P		I [A]	n [1/min]	M [Nm]	NOM. EFF at ... load [%]			Power factor at ... load			I _A /I _N I _f /I _N	M _k /M _N T _f /T _N	M _v /M _N T _v /T _N	IE-CL
			[kW]	[hp]				4/4	3/4	2/4	4/4	3/4	2/4				
400	Δ	50	7.50	- / -	15.40	1450	49.0	86.0	86.5	85.4	0.82	0.76	0.64	6.6	2.6	3.1	IE1
690	Y	50	7.50	- / -	8.90	1450	49.0	86.0	86.5	85.4	0.82	0.76	0.64	6.6	2.6	3.1	IE1
460	Δ	60	8.60	- / -	14.70	1750	47.0	87.5	87.8	86.7	0.84	0.79	0.68	7.0	2.4	3.0	IE1

IM B3 / IM 1001		FS 132 M	44 kg	IP55	CC032A	IEC/EN 60034	IEC, DIN, ISO, VDE, EN
-----------------	--	----------	-------	------	--------	--------------	------------------------

Mechanical data		Terminal box	
Sound pressure level 50Hz/60Hz (load)	64 dB(A) 68 dB(A)	Terminal box position	top
Moment of inertia	0.024 kg m ²	Material of terminal box	Aluminium
Bearing DE NDE	6208 2Z C3 6208 2Z C3	Type of terminal box	TB1 H00
Bearing lifetime	40000 h	Contact screw thread	M4
Lubricants	Esso Unirex N3	Max. cross-sectional area	6.0 mm ²
Regreasing device	No	Cable diameter from ... to ...	11.0 mm - 21.0 mm
Grease nipple	- / -	Cable entry	2xM32x1,5
Type of bearing	Preloaded bearing DE	Cable gland	2 plugs
Condensate drainage holes	No	Special design (0)	
External earthing terminal			
Vibration class	A		
Insulation	155(F) to 130(B)		
Duty type	S1		
Direction of rotation	bidirectional		
Frame material	aluminum		
Data of anti condensation heating	- / -		
Coating (paint finish)	Standard paint finish C2		
Color, paint shade	RAL7030		
Motor protection	(A) without (Standard)		
Method of cooling	IC411 - self ventilated, surface cooled		
Environmental conditions			
Ambient temperature	-20 °C - +40 °C		
Altitude above sea level	1000 m		

