

MF5600 Detachable Display Gas Flow Meters

15 years of independent R & D and production of flowmeter





- ✓ Franchise agent

✓ OEM


✓ Sufficient supply



Specification

item	val	value			
Model Number	MF5612	MF5619			
Diameter	12mm	19mm			
Maximum flow	200,300SLPM	600,800SLPM			
Initiating flow	0.3SLPM	0.8SLPM			
Range than	30:	30:1			
Precision	±(2.0+0.	±(2.0+0.5FS)%			
Repetitive	0.5	0.5%			
Maximum working pressure	≤1.01	≤1.0MPa			
Working temperature	-10~+	-10~+55°C			
Humidity	<95%RH(no	<95%RH(no ice,no frost)			
Working power supply	12~24VD	12~24VDC,50mA			
Temperature	4~20mA; RS48	4~20mA; RS485; 3.3V pulse			
Mechanical interface	NPT1/2"	NPT3/4"			
Calibration conditions	Air(20°C,10	Air(20°C,101.325kPa)			
Protection grade	IP ²	IP40			

LCD display



Clear and intuitive, convenient reading



Product features

- 1. The split display can be installed away from the gas line through a specially designed connection cable.
- 2. The meter standard is equipped with RS485 communication module, which is equipped with 4-20mA standard current output and pulse output.
- 3. Smooth stainless steel tube for oxygen measurement.
- 4. Super-large range is helpful for accurate monitoring of gas flow.
- 5. Multiple connection modes are optional, convenient to install.

Measuring medium

It can be widely used in petroleum, gas, chemical industry, smelting, energy and other fields; it can also be used for medical oxygen measurement in hospital oxygen supply system.













Product size



model selection



^{*} There is flow rate number only for unit SLPM. If other unit is selected, there must be flow rate number with unit together. For CO₂, selectable: 200 SLPM (without 300 SLPM) for MF5612; 600 SLPM (without 800 SLPM) for MF5619.

Typical flow range:

Model	DN	Connection	Flow Range		
			SLPM	SCFM	NCMH
MF5612	12mm	1/2-	200	7	12
			300	10.5	18
MF5619	19mm	3/4-	600	21	36
			800	28	48

Attachment



Wiring 1: user input/output interface cable (Model:IC7-150)



Wiring 2: LCD cable connection (Model:IC7-30-IC7,Length:30cm, Model:IC7-200-IC7,Length:2cm)