



MLFB-Ordering data: 1LE1502-2DA03-4AA4

Motor type: 1CV1280A

Client order no.:

Item no.:

Order no.:

Consignment no.:

Offer no.:

Project:

Remarks:

U [V]	Δ/Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	NOM. EFF at ... load [%]			Power factor at ... load			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4	I _Δ /I _N	T _Δ /T _N	T _β /T _N	
400	Δ	50	75.00	- / -	136.00	2975	241.0	92.7	92.5	91.3	0.86	0.83	0.74	6.8	2.2	3.0	IE1
690	Y	50	75.00	- / -	79.00	2975	241.0	92.7	92.5	91.3	0.86	0.83	0.74	6.8	2.2	3.0	IE1
460	Δ	60	84.00	- / -	130.00	3575	224.0	93.0	92.6	91.1	0.87	0.84	0.77	7.0	2.4	3.0	IE1

IM B3 / IM 1001		FS 280 S	470 kg	IP55	CC032A	IEC/EN 60034	IEC, DIN, ISO, VDE, EN
-----------------	--	----------	--------	------	--------	--------------	------------------------

Mechanical data		Terminal box	
Sound pressure level 50Hz/60Hz (load)	72 dB(A) 77 dB(A)	Terminal box position	top
Moment of inertia	0.72 kg m ²	Material of terminal box	cast iron
Bearing DE NDE	6315 C3 6315 C3	Type of terminal box	TB1 N01
Relubrication interval/quantity	25 g 25 g 4000 h	Contact screw thread	M10
Lubricants	Esso Unirex N3	Max. cross-sectional area	120.0 mm ²
Regreasing device	Yes (standard)	Cable diameter from ... to ...	34.0 mm - 42.0 mm
Grease nipple	M10x1 DIN 3404 A	Cable entry	2xM63x1,5
Type of bearing	Locating bearing NDE	Cable gland	2 plugs
Condensate drainage holes	Yes (standard)	Special design (0)	
External earthing terminal	Yes (standard)		
Vibration class	A		
Insulation	155(F) to 130(B)		
Duty type	S1		
Direction of rotation	bidirectional		
Frame material	cast iron		
Data of anti condensation heating	-/-		
Coating (paint finish)	Standard paint finish C2		
Color, paint shade	RAL7030		
Motor protection	(A) without (Standard)		
Method of cooling	IC411 - self ventilated, surface cooled		
Environmental conditions			
Ambient temperature	-20 °C - +40 °C		
Altitude above sea level	1000 m		