



MLFB-Ordering data: 1LE1002-1DC23-4AA4

Motor type: 1AV1162C

Client order no.:

Item no.:

Order no.:

Consignment no.:

Offer no.:

Project:

Remarks:

U [V]	Δ/Y	f [Hz]	P		I [A]	n [1/min]	M [Nm]	NOM. EFF at ... load [%]			Power factor at ... load			I _A /I _N	M _k /M _N	M _k /M _N	IE-CL
			[kW]	[hp]				4/4	3/4	2/4	4/4	3/4	2/4	I _β /I _N	T _β /T _N	T _β /T _N	
400	Δ	50	7.50	- / -	17.50	970	74.0	84.7	84.8	83.2	0.73	0.66	0.54	5.5	2.1	2.9	IE1
690	Y	50	7.50	- / -	10.20	970	74.0	84.7	84.8	83.2	0.73	0.66	0.54	5.5	2.1	2.9	IE1
460	Δ	60	8.60	- / -	16.70	1170	70.0	86.0	86.0	84.5	0.75	0.68	0.57	5.9	2.2	2.9	IE1

IM B3 / IM 1001		FS 160 M	72 kg	IP55	CC032A	IEC/EN 60034	IEC, DIN, ISO, VDE, EN
-----------------	--	----------	-------	------	--------	--------------	------------------------

Mechanical data		Terminal box	
Sound pressure level 50Hz/60Hz (load)	67 dB(A) 70 dB(A)	Terminal box position	top
Moment of inertia	0.056 kg m ²	Material of terminal box	Aluminium
Bearing DE NDE	6209 2Z C3 6209 2Z C3	Type of terminal box	TB1 J00
Bearing lifetime	40000 h	Contact screw thread	M5
Lubricants	Esso Unirex N3	Max. cross-sectional area	16.0 mm ²
Regreasing device	No	Cable diameter from ... to ...	19.0 mm - 28.0 mm
Grease nipple	- / -	Cable entry	2xM40x1,5
Type of bearing	Locating bearing NDE	Cable gland	2 plugs
Condensate drainage holes	No	Special design (0)	
External earthing terminal			
Vibration class	A		
Insulation	155(F) to 130(B)		
Duty type	S1		
Direction of rotation	bidirectional		
Frame material	aluminum		
Data of anti condensation heating	- / -		
Coating (paint finish)	Standard paint finish C2		
Color, paint shade	RAL7030		
Motor protection	(A) without (Standard)		
Method of cooling	IC411 - self ventilated, surface cooled		
Environmental conditions			
Ambient temperature	-20 °C - +40 °C		
Altitude above sea level	1000 m		



کالا صنعتی تنها یک فروشگاه نیست!
آموزش، انتخاب، خرید