



# 4.248 (Roller Compactor)



Max Power	56 kW at 2200 rpm	ماکزیمم قدرت
Max Torque	281 N.m at 1400 rpm	ماکزیمم گشتاور



## Basic Technical Data

Bore: 101 mm  
 Stroke: 127 mm  
 Number of cylinder: 4 , Inline  
 Cubic capacity: 4.07 litres  
 Induction system: Naturally Aspirated  
 Combustion system: Direct Injection  
 Compression ratio: 16:1  
 Cooling: Liquid  
 Electrical system: 12V  
 Power take off (P.T.O): Additional crankshaft V belt pulley or axial P.T.O choice of two optional timing case P.T.O position.  
 Weight: \* 290 kg

## مشخصات فنی

قطر سیلندر: ۱۰۱ میلی‌متر  
 کورس پیستون: ۱۲۷ میلی‌متر  
 تعداد سیلندر: چهار سیلندر خطی  
 ظرفیت حجمی: ۴/۰۷ لیتر  
 سیستم ورودی هوا: تنفس طبیعی  
 سیستم احتراق: پاشش مستقیم  
 نسبت تراکم: ۱۶:۱  
 سیستم خنک کاری: بوسیله آب  
 سیستم الکتریکی: ۱۲ ولت  
 جذب قدرت فرعی: پولی میل‌لنگ با شیار V شکل اضافی و یا شفت P.T.O از طریق چرخنده‌های سیستم تایمینگ  
 وزن: \* ۲۹۰ کیلوگرم

## Overall Dimensions\*

Length: 810 mm  
 Width: 548.4 mm  
 Height: 748.5 mm  
 \* Approximate only and depends on application.

## ابعاد کلی\*

طول: ۸۱۰ میلی‌متر  
 عرض: ۵۴۸/۴ میلی‌متر  
 ارتفاع: ۷۴۸/۵ میلی‌متر  
 \* مقادیر تقریبی بوده و بسته به کاربرد موتور متغیر می باشد.

